



50 MHz Phase Locked Crystal Oscillator, 10 MHz
External Ref., Phase Noise -155 dBc/Hz, SMA

Phase Locked Crystal Oscillators Technical Data

PE19XP5002

Features

- 50 MHz Phase-Locked Crystal Oscillator
- External 10 MHz Reference Oscillator
- -155 dBc/Hz @ 10kHz offset
- Pout = +7 dBm
- Harmonics = -20 dBc
- SMA connector
- Designed to meet MIL-STD-202 Environmental Conditions
- SMT version available see PE19XP5000

Applications

- Phase Locked Loop
- Function Generators
- Frequency Synthesizers
- Receivers
- Electronic Jamming Equipment
- Local Oscillator
- Wireless Communications
- SATCOM
- Optical Communications
- Military Electronic Systems

Description

The PE19XP5002 is a 50 MHz Phase-Locked Crystal Oscillator with an external 10 MHz Reference Oscillator. This design features exceptional phase noise performance of -155 dBc/Hz @ 10 kHz offset. Supply Voltage is +12VDC @ 75 mA typ. The package is a connectorized module with Lock Detect and SMA connectors. The reference oscillator has an output power level of +7 dBm +/- 2 dB and 2nd harmonic output of -20 dBc typical. The Reference Oscillator operates over a temperature range of -30°C to +70°C and is designed to meet MIL-STD-202 test conditions for Vibration and Shock.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Output Frequency		50		MHz
Output Impedance		50		Ohms
Output Power	+5	+7	+9	dBm
Phase Noise @ 10Hz Offset		-90	-85	dBc/Hz
Phase Noise @ 100Hz Offset		-105	-100	dBc/Hz
Phase Noise @ 1kHz Offset		-135	-130	dBc/Hz
Phase Noise @ 10kHz Offset		-155	-150	dBc/Hz
Reference Frequency		10		MHz
Reference Impedance		50		Ohms
Reference Power	+4	+7	+10	dBm
Reference Phase Noise @ 10Hz Offset		-105		dBc/Hz
Reference Phase Noise @ 100Hz Offset		-135		dBc/Hz
Reference Phase Noise @ 1kHz Offset		-145		dBc/Hz
2nd Harmonics		-20	-15	dBc
Spurious		-70	-65	dBc
Lock Detect	5 VDC TTL, HIGH=LOCK			
Supply Voltage (DC) 1		12		Vdc

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 MHz Phase Locked Crystal Oscillator, 10 MHz External Ref., Phase Noise -155 dBc/Hz, SMA PE19XP5002](#)



50 MHz Phase Locked Crystal Oscillator, 10 MHz
External Ref., Phase Noise -155 dBc/Hz, SMA

Phase Locked Crystal Oscillators Technical Data

PE19XP5002

Supply Current (DC) 1

75

95

mA

Mechanical Specifications

Size

Length

2 in [50.8 mm]

Width

1.5 in [38.1 mm]

Height

0.6 in [15.24 mm]

Weight

0.102 lbs [46.27 g]

Body Material and Plating

Aluminum

Configuration

Design

Commercial

Reference Type

External

Package Style

Connectorized

Input Connector

SMA Female

Output Connector

SMA Female

Environmental Specifications

Temperature

Operating Range

-30 to +70 deg C

Shock

IAW MIL-STD-202, Method 213, Condition A

Vibration

IAW MIL-STD-202, Method 204, Condition A

ESD Sensitivity

ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in ESD Workstation.



Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 MHz Phase Locked Crystal Oscillator, 10 MHz External Ref., Phase Noise -155 dBc/Hz, SMA PE19XP5002](#)





50 MHz Phase Locked Crystal Oscillator, 10 MHz
External Ref., Phase Noise -155 dBc/Hz, SMA


Phase Locked Crystal Oscillators Technical Data

PE19XP5002

Functional Block Diagram



Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 MHz Phase Locked Crystal Oscillator, 10 MHz External Ref., Phase Noise -155 dBc/Hz, SMA PE19XP5002](#)



50 MHz Phase Locked Crystal Oscillator, 10 MHz
External Ref., Phase Noise -155 dBc/Hz, SMA

Phase Locked Crystal Oscillators Technical Data

PE19XP5002

50 MHz Phase Locked Crystal Oscillator, 10 MHz External Ref., Phase Noise -155 dBc/Hz, SMA from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 MHz Phase Locked Crystal Oscillator, 10 MHz External Ref., Phase Noise -155 dBc/Hz, SMA PE19XP5002](https://www.pasternack.com/50-mhz-phase-locked-crystal-oscillator-external-pe19xp5002-p.aspx)

URL: <https://www.pasternack.com/50-mhz-phase-locked-crystal-oscillator-external-pe19xp5002-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE19XP5002 CAD Drawing

50 MHz Phase Locked Crystal Oscillator, 10 MHz External
Ref., Phase Noise -155 dBc/Hz, SMA



STANDARD TOLERANCES
.X ±0.2
.XX ±0.01
.XXX ±0.005

*STANDARD TOLERANCES APPLY
ONLY TO DIMENSIONS IN INCHES



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE19XP5002

CAGE CODE 53919

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE 082817

SCALE N/A

SIZE A

9999