



50 Ohm 8 Way SMA Wilkinson Power Divider From 500 MHz to 2 GHz Rated at 30 Watts

TECHNICAL DATA SHEET

PE2086

50 Ohm 8 Way SMA Wilkinson Power Divider From 500 MHz to 2 GHz Rated at 30 Watts

Input Connector SMA Female
Output Connectors SMA Female
Frequency Range, GHz 0.5 to 2
Design Wilkinson
Number of Output Ports 8

Electrical Specifications

Frequency Range, GHz 0.5 to 2 Impedance, Ohms 50 Maximum Insertion Loss, dB 1.5 Maximum Input Power, Watts 30 Maximum Input VSWR 1.4:1 Maximum Output VSWR 1.3:1 Minimum Isolation, dB 20 Phase Balance, Degrees ± 4 Flatness, dB 0.4

Mechanical Specifications

Temperature

Operating Range, deg C -55 to +85 Storage Range, deg C -55 to +100

Size

 Length, in [mm]
 4.06 [103.12]

 Width, in [mm]
 4.25 [107.95]

 Height, in [mm]
 0.39 [9.91]

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

50 Ohm 8 Way SMA Wilkinson Power Divider From 500 MHz to 2 GHz Rated at 30 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 8 Way SMA Wilkinson Power Divider From 500 MHz to 2 GHz Rated at 30 Watts PE2086

URL: http://www.pasternack.com/8-way-sma-wilkinson-power-divider-500-mhz-2-ghz-30-watts-pe2086-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

