



Directional 10 dB SMA Coupler From 1 GHz to 4 GHz Rated to 50 Watts

Couplers Technical Data Sheet

PE2CP005-10

Features

- Directional Coupler
- 1 to 4 GHz Frequency Range
- Coupling 10 \pm 1 dB
- Directivity > 20 dB
- VSWR < 1.2:1
- Max Power 50 Watts (CW)

Applications

- Test and Measurement
- Military Communications
- Commercial Communications
- Wireless Communications
- SATCOM

Description

Directional couplers are indispensable components for isolating, separating and combining signals. For example, they provide a simple way of sampling microwave signals. They also can make accurate attenuator measurements since reflections are eliminated. The PE2CP005-10 is a 10 dB directional coupler that operates from 1 to 4 GHz with 20 dB directivity minimum and 1.2:1 VSWR maximum. The package interface uses SMA female connectors, and is also RoHS compliant.

The PE2CP005-10 is part of Pasternack's family of directional/dual-directional couplers that offer coupling ratio up to 50 dB with excellent performance featuring high directivity, low insertion loss and VSWR. They are available in both narrow and broad bandwidths and can be used in a wide variety of applications including signal sampling, VSWR measurements, power combining and distribution.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-----------------------|---------|------------|-----------|-------|
| Frequency Range | 1 | | 4 | GHz |
| Impedance | | 50 | | Ohms |
| Coupling | | 10 \pm 1 | | dB |
| Frequency Sensitivity | | | \pm 0.7 | dB |
| Insertion Loss | | 0.5 | | dB |
| Directivity | 20 | | | dB |
| Main Line VSWR | | | 1.2:1 | |
| Input Power (CW) | | | 50 | Watts |

Electrical Specification Notes:
Values at 25°C, sea level.

Mechanical Specifications

Size

| | |
|------------|----------------------|
| Length | 2.87 in [72.9 mm] |
| Width/Dia. | 0.59 in [14.99 mm] |
| Height | 0.43 in [10.92 mm] |
| Weight | 0.0975 lbs [44.23 g] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 10 dB SMA Coupler From 1 GHz to 4 GHz Rated to 50 Watts PE2CP005-10](#)



Directional 10 dB SMA Coupler From 1 GHz
to 4 GHz Rated to 50 Watts

Couplers Technical Data Sheet

PE2CP005-10

Configuration

Package Type
Input Connector
Output Connector
Coupled Connectors

Connectorized
SMA Female
SMA Female
SMA Female

Environmental Specifications

Temperature

Operating Range
Storage Range

-55 to +85 deg C
-55 to +100 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Directional 10 dB SMA Coupler From 1 GHz to 4 GHz Rated to 50 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 10 dB SMA Coupler From 1 GHz to 4 GHz Rated to 50 Watts PE2CP005-10](#)

URL: <https://www.pasternack.com/directional-10-db-sma-coupler-4-ghz-pe2cp005-10-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE2CP005-10 CAD Drawing

Directional 10 dB SMA Coupler From 1 GHz to 4 GHz Rated to 50 Watts



NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
 PE2CP005-10

PASTERNAK®
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAGE CODE 53919

CAD FILE 07/18/18 SCALE N/A SIZE A 7316