




BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax

RF Cable Assembly Breakouts - PE3000-24

Configuration

- Connector 1: BNC Male
- Connector 2: Banana Plug
- Cable Type: RG58



Mechanical Specifications

Cable Assembly Length Diameter

Weight Cable Color Connection Type One Time Minimum Bend Radius

Cable

Cable Type Impedance Dielectric Type Number of Shields Shield Layer 1 Jacket Material Jacket Diameter 24 in [609.6 mm] 1.175 in [29.85 mm] 0.123 lbs [55.79 g] Black Between Series 2 in [50.8 mm]

RG58 50 Ohms PE 1 Tinned Copper Braid PVC (NC) 0.195 in [4.95 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax PE3000-24

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved





BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax

RF Cable Assembly Breakouts - PE3000-24

Connectors

Description	Connector 1	Connector 2
Туре	BNC Male	Banana Plug
Specification	MIL-STD-348A	
Impedance	50 Ohms	0 Ohms
Connection Method	Standard	Standard
Contact Material and Plating	Brass, Gold	Brass, Nickel
Contact Plating Specification	30µ in. minimum	
Dielectric Type	Teflon	ABS
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100µ in. minimum	

Environmental Specifications

Temperature Operating Range

-40 to +80 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax PE3000-24

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved





BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax

RF Cable Assembly Breakouts - PE3000-24

How to Order **PE3000** Part Number Configuration: - XX uu - Unit of Measure: cm = Centimeters <blank> = Inches Length **Base Number** PE3000-12 = 12 inches long cable Example: PE3000-100cm = 100 cm long cable BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax PE3000-24 URL: https://www.pasternack.com/bnc-male-banana-plug-rg58cu-cable-assembly-pe3000-24-p.aspx The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved

PE3000-24 CAD Drawing BNC Male to Banana Plugs Cable 24 Inch Length Using RG58 Coax

