





Description

Pasternack's PE3172-6 SMA male to SMB plug 6 inch cable using RG58 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMA to SMB cable assembly has a male to plug gender configuration with 50 ohm flexible RG58 coax. The PE3172-6 SMA male to SMB plug cable assembly operates to 4 GHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMB Plug Cable 6 Inch Length Using RG58 Coax PE3172-6

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved



C. STERNA P.

RF Cable Assemblies Technical Data Sheet

PE3172-6

Electrical Specifications

Description Frequency Range		Minimu	Minimum Ty		Maximum 4	Units GHz
		DC				
VSWR					1.4:1	
Velocity of Propagation				65.9		%
Capacitance		30.8 [101.05]			pF/ft [pF/m]	
Operating Voltage (AC)					335	Vrms
Specifications by Fr	equency					
Specifications by Fro	equency F1	F2	F3	F4	F5	Units
		F2 0.25	F3 0.5	F4 1	F5 4	Units GHz
Description	F1					
Description Frequency	F1 0.1	0.25	0.5	1	4	GHz

Mechanical Specifications

Cable Assembly Length* 6 in [152.4 mm] Diameter 0.315 in [8 mm] Weight 0.041 lbs [18.6 g] Cable Cable Type **RG58** Impedance 50 Ohms Inner Conductor Type Stranded Inner Conductor Material and Plating Copper, Tin ΡE **Dielectric Type** Number of Shields 1 **Tinned Copper Braid** Shield Layer 1 **Jacket Material** PVC (NC), Black Jacket Diameter 0.195 in [4.95 mm] One Time Minimum Bend Radius 0.98 in [24.89 mm] Repeated Minimum Bend Radius 1.96 in [49.78 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMB Plug Cable 6 Inch Length Using RG58 Coax PE3172-6

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved



RF Cable Assemblies Technical Data Sheet

PE3172-6

Connectors

Description	Connector 1	Connector 2	
Туре	SMA Male	SMB Plug	
Specification	MIL-STD-348A	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms	
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold	
Contact Plating Specification	50 µin minimum	30 µin minimum	
Dielectric Type	PTFE	PTFE	
Body Material and Plating	Brass, Nickel	Brass, Nickel	
Body Plating Specification	100 µin minimum	100 µin minimum	
Coupling Nut Material and Plating	Brass, Nickel		
Coupling Nut Plating Specification	100 µin minimum		
Hex Size	5/16 inch		
Torque	3 in-lbs [0.34 Nm]		

Environmental Specifications

Temperature Operating Range

-40 to +80 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

- Notes:
- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMB Plug Cable 6 Inch Length Using RG58 Coax PE3172-6

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved





RF Cable Assemblies Technical Data Sheet

PE3172-6

How to Order **PE3172** Part Number Configuration: - XX uu - Unit of Measure: cm = Centimeters <blank> = Inches Length Base Number Example: PE3172-12 = 12 inches long cable PE3172-100cm = 100 cm long cable SMA Male to SMB Plug Cable 6 Inch Length Using RG58 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMB Plug Cable 6 Inch Length Using RG58 Coax PE3172-6 URL: https://www.pasternack.com/sma-male-smb-plug-rg58cu-cable-assembly-pe3172-6-p.aspx The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

PE3172-6 CAD Drawing SMA Male to SMB Plug Cable 6 Inch Length Using RG58 Coax

