



# SMA Male to N Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS

## TECHNICAL DATA SHEET

PE33231-60

### SMA Male to N Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS

#### Configuration

Connector 1	SMA Male
Connector 2	N Male
Cable Type	150 Series

#### Electrical Specifications

Frequency Range, GHz	DC to 18
Impedance, Ohms	50
Maximum VSWR	1.4:1
Velocity of Propagation, %	69.5
RF Shielding, dB	90
Maximum Operating Voltage, Vrms	1,900

#### Typical Electrical Specifications

##### Frequency 1

Frequency, GHz	2
VSWR	1.1:1
Insertion Loss	0.22 dB/ft [ 0.72 dB/m ]

##### Frequency 2

Frequency, GHz	6
VSWR	1.08:1
Insertion Loss	0.34 dB/ft [ 1.12 dB/m ]

##### Frequency 3

Frequency, GHz	10
VSWR	1.17:1
Insertion Loss	0.45 dB/ft [ 1.48 dB/m ]

##### Frequency 4

Frequency, GHz	14
VSWR	1.23:1
Insertion Loss	0.57 dB/ft [ 1.87 dB/m ]

##### Frequency 5

Frequency, GHz	18
VSWR	1.25:1
Insertion Loss	0.68 dB/ft [ 2.23 dB/m ]

#### Electrical Specification Notes:

Short lengths up to 24" long may exhibit VSWR measurements up to 9% higher.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to N Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE33231-60](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to N Male Precision Cable 60 Inch  
Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE33231-60

**Mechanical Specifications**

**Cable Assembly**

Cable Type 150 Series

**Temperature**

Temperature Operating Range, deg C -55 to +205

**Size**

Length, in [cm] 60 [152.4]

One Time Minimum Bend Radius, in [mm] 1 [25.4]

**Cable**

Center Conductor Type Solid  
Cable Inner Conductor Copper Clad Steel, Silver  
No of Shields 1  
Dielectric Type PTFE  
Jacket Material FEP  
Jacket Diameter, in [mm] 0.15 [3.81]

**Connector 1**

Type SMA Male  
Configuration Straight  
Inner Conductor Material and Plating Copper Clad Steel, Silver  
Coupling Nut Material and Plating Passivated Stainless Steel  
Hex Size, in. 5/16  
Torque, in-lbs [Nm] 8 [0.9]  
Body Material and Plating Passivated Stainless Steel  
Dielectric Type PTFE

**Connector 2**

Type N Male  
Configuration Straight  
Inner Conductor Material and Plating Gold  
Outer Conductor Material and Plating Passivated Stainless Steel  
Coupling Nut Material and Plating Brass, Nickel  
Body Material and Plating Passivated Stainless Steel  
Dielectric Type PTFE

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to N Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE33231-60](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to N Male Precision Cable 60 Inch  
Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE33231-60

**Plotted and Other Data**

Notes:

Values at 25 °C, sea level

SMA Male to N Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to N Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE33231-60](http://www.pasternack.com/sma-male-n-male-150-series-cable-assembly-pe33231-60-p.aspx)


URL: <http://www.pasternack.com/sma-male-n-male-150-series-cable-assembly-pe33231-60-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE33231-60 CAD Drawing

SMA Male to N Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS

Standard Lengths	
-12	12"
-24	24"
-36	36"
-48	48"
-60	60"
-XXX	Custom Length in Inches



NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].  
4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $3/8"$ , WHICHEVER IS GREATER.

DWG TITLE  
**PE33231-XX**

PASTERNAK ENTERPRISES, INC.  
P.O. BOX 16759, IRVINE, CA 92623  
PHONE (949) 261-1920 FAX (949) 261-7451  
WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)  
COAXIAL & FIBER OPTICS



REV. A	FSCM NO. 53919	CAD FILE 030508	SCALE N/A	SIZE A	127
--------	----------------	-----------------	-----------	--------	-----