

BNC Male to BNC Male Cable 48 Inch Length Using 95 Ohm RG180 Coax



## **TECHNICAL DATA SHEET**

# PE33574-48

#### Configuration

Connector 1 Connector 2 Cable Type

#### **Electrical Specifications**

Frequency Range Impedance Velocity of Propagation Dielectric Withstanding Voltage (AC)

#### **Mechanical Specifications**

**Size** Length Diameter

Weight Cable Color

Cable

Cable Type Inner Conductor Type Cable Inner Conductor No of Shields Dielectric Type Jacket Material Jacket Diameter

#### **Connector 1**

Type Configuration Inner Conductor Material and Plating Inner Conductor Plating Specification Coupling Nut Material and Plating Coupling Nut Plating Specification Body Material and Plating Body Plating Specification Dielectric Type

#### **Connector 2**

Type Configuration Inner Conductor Material and Plating Inner Conductor Plating Specification Coupling Nut Material and Plating Coupling Nut Plating Specification BNC Male BNC Male RG180

DC to 3 GHz 50 Ohms 70 % 1,500 Vrms

48 in [121.92 cm] 0.57 in [14.48 mm] 0.045 lbs [20.41 g] Tan

RG180 Stranded Copper Clad Steel, Silver 1 PTFE FEP 0.145 in [3.68 mm]

BNC Male Straight Brass, Gold 30µ in. minimum Brass, Nickel 100µ in. minimum Brass, Nickel 100µ in. minimum Teflon

BNC Male Straight Brass, Gold 30µ in. minimum Brass, Nickel 100µ in. minimum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Male to BNC Male Cable 48 Inch Length Using 95 Ohm RG180 Coax PE33574-48

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





**PE33574-48** 

# BNC Male to BNC Male Cable 48 Inch Length Using 95 Ohm RG180 Coax

# Brass, Nickel 100µ in. minimum Teflon 12/19/2011

Body Material and Plating **Body Plating Specification Dielectric Type** 

Compliance Certifications (visit www.Pasternack.com for current document) For RoHS Compliant version, use PE33574LF-48. Contact Pasternack if product cannot be found. **REACH Compliant** 


### **Plotted and Other Data**

- Notes: Values at +25 °C, sea level

#### How to Order

**TECHNICAL DATA SHEET** 

Part Number Configuration:



Example: PE33574-12 = 12 inches long cable PE33574-100cm = 100 cm long cable

BNC Male to BNC Male Cable 48 Inch Length Using 95 Ohm RG180 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: BNC Male to BNC Male Cable 48 Inch Length Using 95 Ohm RG180 Coax PE33574-48

URL: http://www.pasternack.com/bnc-male-bnc-male-rg180bu-cable-assembly-pe33574-48-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

PE33574-48 CAD Drawing BNC Male to BNC Male Cable 48 Inch Length Using 95 Ohm RG180 Coax

