



SMA Male to SMA Male Cable Using PE-SR402AL Coax

RF Cable Assemblies Technical Data Sheet

PE34180LF

Configuration

- Connector 1: SMA Male
- Connector 2: SMA Male
- Cable Type: PE-SR402AL

Features

- Max Frequency 18 GHz


Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE34180LF SMA male to SMA male cable using PE-SR402AL coax is part of our full line of RF components available for same-day shipping. Pasternack's semi-rigid RF cable assemblies are ideal for high performance applications and can be formed, using proper tooling, to the routing pattern required. This Pasternack SMA to SMA cable assembly has a male to male gender configuration with 50 ohm semi-rigid PE-SR402AL coax. The PE34180LF SMA male to SMA male cable assembly operates to 18 GHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-SR402AL Coax PE34180LF](#)



SMA Male to SMA Male Cable Using PE-SR402AL Coax

RF Cable Assemblies Technical Data Sheet

PE34180LF

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|--------------------------------------|---------|---------|---------|-------|
| Frequency Range | DC | | 18 | GHz |
| VSWR | | | 1.4:1 | |
| Dielectric Withstanding Voltage (AC) | | | 1,000 | Vrms |

Specifications by Frequency

| Description | F1 | F2 | F3 | F4 | F5 | Units |
|-----------------------|------|-------|-------|-------|------|-------|
| Frequency | 1 | 2 | 4.5 | 9 | 18 | GHz |
| Insertion Loss (Typ.) | 0.13 | 0.167 | 0.258 | 0.423 | 0.66 | dB/ft |
| | 0.43 | 0.55 | 0.85 | 1.39 | 2.17 | dB/m |

Mechanical Specifications

Cable Assembly

| | |
|----------|---------------------|
| Diameter | 0.315 in [8 mm] |
| Weight | 0.034 lbs [15.42 g] |

Cable

| | |
|--------------------------------------|---------------------------|
| Cable Type | PE-SR402AL |
| Impedance | 50 Ohms |
| Inner Conductor Type | Solid |
| Inner Conductor Material and Plating | Copper Clad Steel, Silver |
| Dielectric Type | PTFE |
| Number of Shields | 1 |
| Shield Layer 1 | Tinned Aluminum |
| Jacket Diameter | 0.141 in [3.58 mm] |
| One Time Minimum Bend Radius | 0.1 in [2.54 mm] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-SR402AL Coax PE34180LF](#)



SMA Male to SMA Male Cable Using PE-SR402AL Coax

RF Cable Assemblies Technical Data Sheet

PE34180LF

Connectors

| Description | Connector 1 | Connector 2 |
|------------------------------------|-----------------------|-----------------------|
| Type | SMA Male | SMA Male |
| Specification | MIL-STD-348A | MIL-STD-348A |
| Impedance | 50 Ohms | 50 Ohms |
| Contact Material and Plating | Brass, Gold | Brass, Gold |
| Contact Plating Specification | 50μ in. minimum | 50μ in. minimum |
| Dielectric Type | Teflon | Teflon |
| Body Material and Plating | Stainless Steel, Gold | Stainless Steel, Gold |
| Body Plating Specification | 10μ in. minimum | 10μ in. minimum |
| Coupling Nut Material and Plating | Brass, Nickel | Brass, Nickel |
| Coupling Nut Plating Specification | 100μ in. minimum | 100μ in. minimum |
| Hex Size | 5/16 in | 5/16 in |
| Torque | 5 in-lbs [0.57 Nm] | 5 in-lbs [0.57 Nm] |

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-SR402AL Coax PE34180LF](#)



SMA Male to SMA Male Cable Using PE-SR402AL Coax

RF Cable Assemblies Technical Data Sheet

PE34180LF

How to Order

Part Number Configuration:

PE34180LF

- xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE34180LF-12 = 12 inches long cable
PE34180LF-100cm = 100 cm long cable

SMA Male to SMA Male Cable Using PE-SR402AL Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-SR402AL Coax PE34180LF](#)


URL: <https://www.pasternack.com/sma-male-sma-male-pe-sr402al-cable-assembly-pe34180lf-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE34180LF CAD Drawing

SMA Male to SMA Male Cable Using PE-SR402AL Coax

| Standard Lengths | |
|------------------|-------------------------|
| -12 | 12" |
| -24 | 24" |
| -36 | 36" |
| -48 | 48" |
| -60 | 60" |
| -XXX | Custom Length in Inches |



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

DWG TITLE
PE34180-XX

PE PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

| | | | | | |
|--------|----------------|-----------------|-----------|--------|-----|
| REV. - | FSCM NO. 53919 | CAD FILE 010207 | SCALE N/A | SIZE A | 127 |
|--------|----------------|-----------------|-----------|--------|-----|