

# SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax



# **RF Cable Assemblies Technical Data Sheet**

PE34200-18

# Configuration

· Connector 1: SMA Male

Connector 2: SMA Male Right Angle
Cable Type: PE-SR401AL-STRAIGHT

### **Features**

- Max Frequency 18 GHz
- 69.5% Phase Velocity

# **Applications**

· General Purpose

· Laboratory Use

### Description

Pasternack's PE34200-18 SMA male to SMA male right angle 18 inch cable using PE-SR401AL coax is part of our full line of RF components available for same-day shipping. Pasternack's semi-rigid RF cable assemblies are ideal for high performance applications and can be formed, using proper tooling, to the routing pattern required. This Pasternack SMA to SMA cable assembly has a male to male gender configuration with 50 ohm semi-rigid PE-SR401AL-STRAIGHT coax. The PE34200-18 SMA male to SMA male cable assembly operates to 18 GHz. The right angle SMA interface on the PE-SR401AL-STRAIGHT cable allows for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Velocity of Propagation		69.5		%
Capacitance		29.6 [97.11]		pF/ft [pF/m]
Dielectric Withstanding Voltage (AC)			7,500	Vrms

#### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.4	1	5	10	18	GHz
Insertion Loss (Typ.)	4.5	7.5	22	33	48	dB
Power Handling (Max.)	962	661	265	174	100	W

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax PE34200-18

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



# SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax



# **RF Cable Assemblies Technical Data Sheet**

PE34200-18

#### **Mechanical Specifications**

Cable Assembly

 Length\*
 18 in [457.2 mm]

 Diameter
 0.378 in [9.6 mm]

 Weight
 0.133 lbs [60.33 g]

Cable

Cable Type PE-SR401AL-STRAIGHT Impedance 50 Ohms

Inner Conductor Type Solid

Inner Conductor Material and Plating Copper, Silver Dielectric Type PTFE

Number of Shields 1
Shield Layer 1 Tinned Aluminum
Jacket Diameter 0.25 in [6.35 mm]

One Time Minimum Bend Radius 0.25 in [6.35 mm]

#### **Connectors**

Connector 1	Connector 2		
SMA Male	SMA Male Right Angle		
50 Ohms	50 Ohms		
Gold	Brass, Gold		
PTFE	Teflon		
Brass, Gold	Brass, Gold		
Brass, Nickel	Brass, Gold		
5/16 in.	5/16 in		
5 in-lbs [0.57 Nm]	5 in-lbs [0.57 Nm]		
	SMA Male 50 Ohms Gold PTFE Brass, Gold Brass, Nickel 5/16 in.		

Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.

Cable assemblies that are 60 inches or less use straight coax, greater than 60 inches use coiled coax

## Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax PE34200-18

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



# SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax



# **RF Cable Assemblies Technical Data Sheet**

PE34200-18

#### **How to Order**



PE34200-12 = 12 inches long cable Example:

PE34200-100cm = 100 cm long cable

SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax PE34200-18

URL: https://www.pasternack.com/sma-male-sma-male-pe-sr401al-cable-assembly-pe34200-18-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

PE34200-18 CAD Drawing
SMA Male to SMA Male Right Angle Cable 18 Inch Length Using PE-SR401AL Coax

