

SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax



RF Cable Assemblies Technical Data Sheet

PE34215-36

Configuration

Connector 1: SMA Male Right Angle
Connector 2: SMA Male Right Angle
Cable Type: PE-SR401AL-STRAIGHT

Features

- Max Frequency 8 GHz
- 69.5% Phase Velocity

Applications

· General Purpose

Laboratory Use

Description

Pasternack's PE34215-36 SMA male right angle to SMA male right angle 36 inch cable using PE-SR401AL coax is part of our full line of RF components available for same-day shipping. Pasternack's semi-rigid RF cable assemblies are ideal for high performance applications and can be formed, using proper tooling, to the routing pattern required. This Pasternack SMA to SMA cable assembly has a male to male gender configuration with 50 ohm semi-rigid PE-SR401AL-STRAIGHT coax. The PE34215-36 SMA male to SMA male cable assembly operates to 8 GHz. The right angle SMA interfaces on the PE-SR401AL-STRAIGHT cable allow for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		8	GHz
Velocity of Propagation		69.5		%
Capacitance		29.6 [97.11]		pF/ft [pF/m]
Dielectric Withstanding Voltage (AC)			7,500	Vrms

Specifications by Frequency

GHz
dB
W

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax PE34215-36

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax



RF Cable Assemblies Technical Data Sheet

PE34215-36

Mechanical Specifications

Cable Assembly

 Length*
 36 in [914.4 mm]

 Diameter
 0.378 in [9.6 mm]

 Weight
 0.239 lbs [108.41 g]

Cable

Cable Type PE-SR401AL-STRAIGHT

Impedance 50 Ohms
Inner Conductor Type Solid
Inner Conductor Material and Plating Conductor Material and Plating

Inner Conductor Material and Plating

Dielectric Type

Number of Shields

Copper, Silver
PTFE

1

Shield Layer 1 Tinned Aluminum Jacket Diameter 0.25 in [6.35 mm]

One Time Minimum Bend Radius 0.25 in [6.35 mm]

Connectors

Description	Connector 1	Connector 2 SMA Male Right Angle	
Туре	SMA Male Right Angle		
Impedance	50 Ohms	50 Ohms	
Contact Material and Plating	Brass, Gold	Brass, Gold	
Dielectric Type	Teflon	Teflon	
Body Material and Plating	Brass, Gold	Brass, Gold	
Coupling Nut Material and Plating	Brass, Gold	Brass, Gold	
Hex Size	5/16 in	5/16 in	
Torque	5 in-lbs [0.57 Nm]	5 in-lbs [0.57 Nm]	

Mechanical Specification Notes:

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax PE34215-36

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.

Cable assemblies that are 60 inches or less use straight coax, greater than 60 inches use coiled coax



SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax



RF Cable Assemblies Technical Data Sheet

PE34215-36

How to Order



Example: PE34215-12 = 12 inches long cable

PE34215-100cm = 100 cm long cable

SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax PE34215-36

URL: https://www.pasternack.com/sma-male-sma-male-pe-sr401al-cable-assembly-pe34215-36-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PE34215-36 CAD Drawing SMA Male Right Angle to SMA Male Right Angle Cable 36 Inch Length Using PE-SR401AL Coax

