



N Male to N Female Cable 72 Inch Length Using RG217 Coax

TECHNICAL DATA SHEET

PE34274-72

N Male to N Female Cable 72 Inch Length Using RG217 Coax

Configuration

Connector 1 N Male
Connector 1 Specification MIL-STD-348A
Connector 2 N Female
Connector 2 Specification MIL-C-39012
Cable Type RG217
Impedance, Ohms 50

Mechanical Specifications

Cable Assembly

Cable Type RG217

Temperature

Temperature Operating Range, deg C -40 to +80

Size

 Length, in [cm]
 72 [182.88]

 Diameter, in [mm]
 0.875 [22.23]

 Weight, lbs [g]
 0.549 [249.02]

 Cable Color
 Black

Cable

No of Shields 2
Dielectric Type PE
Jacket Material PVC
Jacket Diameter, in [mm] 0.545 [13.84]

Connector 1

Type N Male Configuration Straight Inner Conductor Material and Plating Brass, Gold Inner Conductor Plating Specification 30µ in. minimum Coupling Nut Material and Plating Brass, Nickel Coupling Nut Plating Specification 100µ in. minimum Body Material and Plating Brass, Nickel **Body Plating Specification** 100µ in. minimum Dielectric Type Teflon

Connector 2

Type N Female
Configuration Straight
Inner Conductor Material and Plating Silver

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male to N Female Cable 72 Inch Length Using RG217 Coax PE34274-72

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

specifications are nominal.





N Male to N Female Cable 72 Inch Length Using RG217 Coax

TECHNICAL DATA SHEET

PE34274-72

Inner Conductor Plating Specification QQ-S-365
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes: Values at 25 °C, sea level

N Male to N Female Cable 72 Inch Length Using RG217 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male to N Female Cable 72 Inch Length Using RG217 Coax PE34274-72

URL: http://www.pasternack.com/n-male-n-female-rg217u-cable-assembly-pe34274-72-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

PE34274-72 CAD Drawing
N Male to N Female Cable 72 Inch Length Using RG217 Coax

