



RF Cable Assemblies Technical Data Sheet

PE34429-12

Configuration

Connector 1: MHV MaleConnector 2: MHV MaleCable Type: RG141

Features

- Max Frequency 300 MHz
- PTFE (FG) Jacket

Applications

· General Purpose

· Laboratory Use

Description

Pasternack's PE34429-12 MHV male to MHV male 12 inch cable using RG141 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack MHV to MHV cable assembly has a male to male gender configuration with 50 ohm flexible RG141 coax. The PE34429-12 MHV male to MHV male cable assembly operates to 300 MHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		300	MHz
VSWR			1.4:1	
Capacitance		29.4 [96.46]		pF/ft [pF/m]
Jacket Spark			2,000	Vrms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MHV Male to MHV Male Cable 12 Inch Length Using RG141 Coax PE34429-12





RF Cable Assemblies Technical Data Sheet

PE34429-12

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	50	100	250	500	1,000	MHz
Insertion Loss (Typ.)	0.224	0.239	0.254	0.279	0.33	dB
VSWR (Max.)	1.4:1	1.4:1	1.4:1	1.4:1	1.4:1	
Return Loss (Max.)	15.56	15.563	15.563	15.563	15.563	dB

Mechanical Specifications

Cable Assembly

Length* Diameter

Weight

Cable

Cable Type Impedance

Inner Conductor Type

Inner Conductor Material and Plating

Dielectric Type Number of Shields Shield Layer 1 Jacket Material

Jacket Diameter

12 in [304.8 mm] 0.57 in [14.48 mm]

0.09 lbs [40.82 g]

RG141 50 Ohms Solid

Copper Clad Steel, Silver

PTFE 1

> Silver Plated Copper PTFE (FG), Beige 0.19 in [4.83 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MHV Male to MHV Male Cable 12 Inch Length Using RG141 Coax PE34429-12





RF Cable Assemblies Technical Data Sheet

PE34429-12

Connectors

Description	Connector 1	Connector 2	
Туре	MHV Male	MHV Male	
Specification	MIL-STD-348	MIL-STD-348	
Impedance	50 Ohms 50 Ohms		
Contact Material and Plating	Brass, Gold	d Brass, Gold	
Contact Plating Specification	30μ In. Min	30μ ln. Min	
Dielectric Type	Teflon	Teflon	
Body Material and Plating	Brass, Nickel	Brass, Nickel	
Body Plating Specification	100μ In. Minimum	100μ ln. Minimum	
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel	
Coupling Nut Plating Specification	100μ ln. Minimum	100µ In. Minimum	

Mechanical Specification Notes:

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

· Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MHV Male to MHV Male Cable 12 Inch Length Using RG141 Coax PE34429-12

^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.





RF Cable Assemblies Technical Data Sheet

PE34429-12

How to Order



Example: PE34429-12 = 12 inches long cable

PE34429-100cm = 100 cm long cable

MHV Male to MHV Male Cable 12 Inch Length Using RG141 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MHV Male to MHV Male Cable 12 Inch Length Using RG141 Coax PE34429-12

URL: https://www.pasternack.com/mhv-male-mhv-male-rg141au-cable-assembly-pe34429-12-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PE34429-12 CAD Drawing
MHV Male to MHV Male Cable 12 Inch Length Using RG141 Coax

