



SC Male to SC Male Cable 72 Inch Length Using RG141 Coax

RF Cable Assemblies Technical Data Sheet

PE34439-72

Configuration

- Connector 1: SC Male
- Connector 2: SC Male
- Cable Type: RG141

Features

- PTFE (FG) Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE34439-72 SC male to SC male 72 inch cable using RG141 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SC to SC cable assembly has a male to male gender configuration with 50 ohm flexible RG141 coax.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Capacitance		29.4 [96.46]		pF/ft [pF/m]
Jacket Spark			2,000	Vrms

Mechanical Specifications

Cable Assembly

Length*	72 in [182.88 cm]
Diameter	0.8 in [20.32 mm]
Weight	0.352 lbs [159.66 g]

Cable

Cable Type	RG141
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	1

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SC Male to SC Male Cable 72 Inch Length Using RG141 Coax PE34439-72](#)



SC Male to SC Male Cable 72 Inch Length Using RG141 Coax

RF Cable Assemblies Technical Data Sheet

PE34439-72

Shield Layer 1
Jacket Material
Jacket Diameter

Silver Plated Copper
PTFE (FG), Beige
0.19 in [4.83 mm]

Connectors

Description	Connector 1	Connector 2
Type	SC Male	SC Male
Specification	MIL-C-39012	MIL-C-39012
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Silver	Silver
Contact Plating Specification	QQ-S-365	QQ-S-365
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Nickel	Brass, Nickel

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SC Male to SC Male Cable 72 Inch Length Using RG141 Coax PE34439-72](#)



SC Male to SC Male Cable 72 Inch Length Using RG141 Coax

RF Cable Assemblies Technical Data Sheet

PE34439-72

How to Order

Part Number Configuration:

PE34439

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE34439-12 = 12 inches long cable
PE34439-100cm = 100 cm long cable

SC Male to SC Male Cable 72 Inch Length Using RG141 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SC Male to SC Male Cable 72 Inch Length Using RG141 Coax PE34439-72](https://www.pasternack.com/sc-male-sc-male-rg141au-cable-assembly-pe34439-72-p.aspx)

URL: <https://www.pasternack.com/sc-male-sc-male-rg141au-cable-assembly-pe34439-72-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE34439-72 CAD Drawing

SC Male to SC Male Cable 72 Inch Length Using RG141 Coax

