



## UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax

### RF Cable Assemblies Technical Data Sheet

PE34589-48

#### Configuration

- Connector 1: UHF Male
- Connector 2: BNC Male
- Cable Type: RG225

#### Features

- Max Frequency 300 MHz
- Double Shielded
- PTFE (FG) Jacket

#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE34589-48 UHF male to BNC male 48 inch cable using RG225 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack UHF to BNC cable assembly has a male to male gender configuration with 50 ohm flexible RG225 coax. The PE34589-48 UHF male to BNC male cable assembly operates to 300 MHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	Error on F1=NULL		Error on F1=NULL	
VSWR			1.4:1	
Capacitance		32.4 [106.3]		pF/ft [pF/m]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax PE34589-48](#)



## UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax

### RF Cable Assemblies Technical Data Sheet

PE34589-48

#### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	50	100	250	500	1,000	MHz
Insertion Loss (Typ.)	0.225	0.25	0.325			dB
VSWR (Max.)	1.4:1	1.4:1	1.4:1	1.4:1	1.4:1	
Return Loss (Max.)	15.56	15.563	15.563	15.563	15.563	dB

#### Mechanical Specifications

##### Cable Assembly

Length*	48 in [121.92 cm]
Diameter	0.7 in [17.78 mm]
Weight	0.827 lbs [375.12 g]

##### Cable

Cable Type	RG225
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	PTFE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	PTFE (FG), Tan
Jacket Diameter	0.43 in [10.92 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax PE34589-48](#)



## UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax

### RF Cable Assemblies Technical Data Sheet

PE34589-48

#### Connectors

Description	Connector 1	Connector 2
Type	UHF Male	BNC Male
Specification		MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30μ in. minimum	30μ in. minimum
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100μ in. minimum	100μ in. minimum
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100μ in. minimum	100μ in. minimum

#### Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8"$ , whichever is greater.

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

##### Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax PE34589-48](#)



## UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax

### RF Cable Assemblies Technical Data Sheet

PE34589-48

#### How to Order

Part Number Configuration:

PE34589

- xx

uu

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE34589-12 = 12 inches long cable  
PE34589-100cm = 100 cm long cable

UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax PE34589-48](https://www.pasternack.com/uhf-male-bnc-male-rg225u-cable-assembly-pe34589-48-p.aspx)

URL: <https://www.pasternack.com/uhf-male-bnc-male-rg225u-cable-assembly-pe34589-48-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE34589-48 CAD Drawing  
UHF Male to BNC Male Cable 48 Inch Length Using RG225 Coax

