



SMA Male Right Angle to SMA Male Right Angle Precision Cable 60 Inch Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE35422-60

SMA Male Right Angle to SMA Male Right Angle Precision Cable 60 Inch Length Using 150 Series Coax, RoHS

Configuration

Connector 1	SMA Male Right Angle
Connector 2	SMA Male Right Angle
Cable Type	150 Series

Electrical Specifications

Frequency Range, GHz	DC to 26.5
Impedance, Ohms	50
Maximum VSWR	1.4:1
Velocity of Propagation, %	69.5
RF Shielding, dB	90
Maximum Operating Voltage, Vrms	1,900

Electrical Specification Notes: Short lengths up to 24" long may exhibit VSWR measurements up to 9% higher.

Mechanical Specifications

Cable Assembly

Cable Type	150 Series
------------	------------

Temperature

Temperature Operating Range, deg C	-50 to +205
------------------------------------	-------------

Size

Length, in [cm]	60 [152.4]
One Time Minimum Bend Radius, in [mm]	1 [25.4]

Cable

Center Conductor Type	Solid
Cable Inner Conductor	Copper Clad Steel, Silver
No of Shields	1
Dielectric Type	PTFE
Jacket Material	FEP
Jacket Diameter, in [mm]	0.15 [3.81]

Connector 1

Type	SMA Male Right Angle
Configuration	Right Angle
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size, in.	5/16

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to SMA Male Right Angle Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE35422-60](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male Right Angle to SMA Male Right Angle Precision
Cable 60 Inch Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE35422-60

Torque, in-lbs [Nm]	8 [0.9]
Body Material and Plating	Passivated Stainless Steel
Dielectric Type	PTFE

Connector 2

Type	SMA Male Right Angle
Configuration	Right Angle
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size, in.	5/16
Torque, in-lbs [Nm]	8 [0.9]
Body Material and Plating	Passivated Stainless Steel
Dielectric Type	PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------


SMA Male Right Angle to SMA Male Right Angle Precision Cable 60 Inch Length Using 150 Series Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to SMA Male Right Angle Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE35422-60](http://www.pasternack.com/sma-male-sma-male-150-series-cable-assembly-pe35422-60-p.aspx)

URL: <http://www.pasternack.com/sma-male-sma-male-150-series-cable-assembly-pe35422-60-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE35422-60 CAD Drawing
 SMA Male Right Angle to SMA Male Right Angle Precision
 Cable 60 Inch Length Using 150 Series Coax, RoHS



**SMA MALE
RIGHT ANGLE**

**SMA MALE
RIGHT ANGLE**

Part Number Configuration		How To Order		Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
PE3	ZZZ YY - xx uu	Examples		-12	12"	-25CM	25Cm
00 - 99999		PE3000LF-100		-24	24"	-50CM	50Cm
LF = RoHS Compliant		PE3000-100		-36	36"	-75CM	75Cm
< Blank > = Standard		PE3000LF-100CM		-48	48"	-100CM	100Cm
Note: LF applies only to RF cables		PE3000-100CM		-60	60"	-125CM	125Cm
				-XX	Custom Length	-XXCM	Custom Length

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].
 4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.

DWG TITLE
PE35422

PE PASTERNAK®
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

FSCM NO. 53919

CAD FILE 122707

SCALE N/A

SIZE A

2233