



7/16 DIN Male to 7/16 DIN Male Cable
12 Inch Length Using RG225 Coax

RF Cable Assemblies Technical Data Sheet

PE36136-12

Configuration

- Connector 1: 7/16 DIN Male
- Connector 2: 7/16 DIN Male
- Cable Type: RG225

Features

- Max Frequency 400 MHz
- Double Shielded
- PTFE (FG) Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE36136-12 7/16 DIN male to 7/16 DIN male 12 inch cable using RG225 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack 7/16 DIN to 7/16 DIN cable assembly has a male to male gender configuration with 50 ohm flexible RG225 coax. The PE36136-12 7/16 DIN male to 7/16 DIN male cable assembly operates to 400 MHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-----------------|---------|--------------|---------|--------------|
| Frequency Range | DC | | 400 | MHz |
| Capacitance | | 32.4 [106.3] | | pF/ft [pF/m] |

Specifications by Frequency

| Description | F1 | F2 | F3 | F4 | F5 | Units |
|-----------------------|-------|-------|-------|-----|-------|-------|
| Frequency | 50 | 100 | 250 | 500 | 1,000 | MHz |
| Insertion Loss (Typ.) | 0.206 | 0.213 | 0.231 | | | dB |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male Cable 12 Inch Length Using RG225 Coax PE36136-12](#)



7/16 DIN Male to 7/16 DIN Male Cable
12 Inch Length Using RG225 Coax

RF Cable Assemblies Technical Data Sheet

PE36136-12

Mechanical Specifications

Cable Assembly

| | |
|----------|----------------------|
| Length* | 12 in [304.8 mm] |
| Diameter | 1.25 in [31.75 mm] |
| Weight | 0.671 lbs [304.36 g] |

Cable

| | |
|--------------------------------------|----------------------------|
| Cable Type | RG225 |
| Impedance | 50 Ohms |
| Inner Conductor Type | Stranded |
| Inner Conductor Material and Plating | Copper, Silver |
| Dielectric Type | PTFE |
| Number of Shields | 2 |
| Shield Layer 1 | Silver Plated Copper Braid |
| Shield Layer 2 | Silver Plated Copper Braid |
| Jacket Material | PTFE (FG), Tan |
| Jacket Diameter | 0.43 in [10.92 mm] |

Connectors

| Description | Connector 1 | Connector 2 |
|------------------------------------|------------------------------|------------------------------|
| Type | 7/16 DIN Male | 7/16 DIN Male |
| Specification | IEC 169-4 | IEC 169-4 |
| Impedance | 50 Ohms | 50 Ohms |
| Contact Material and Plating | Brass/Beryllium Copper, Gold | Brass/Beryllium Copper, Gold |
| Contact Plating Specification | 30μ in. minimum | 30μ in. minimum |
| Dielectric Type | Teflon | Teflon |
| Body Material and Plating | Brass, Nickel | Brass, Nickel |
| Body Plating Specification | 100μ in. minimum | 100μ in. minimum |
| Coupling Nut Material and Plating | Brass, Nickel | Brass, Nickel |
| Coupling Nut Plating Specification | 100μ in. minimum | 100μ in. minimum |
| Hex Size | 32 mm | 32 mm |
| Torque | 18 ft-lbs [24.41 Nm] | 18 ft-lbs [24.41 Nm] |

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male Cable 12 Inch Length Using RG225 Coax PE36136-12](#)



7/16 DIN Male to 7/16 DIN Male Cable
12 Inch Length Using RG225 Coax

RF Cable Assemblies Technical Data Sheet

PE36136-12

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

How to Order

Part Number Configuration:

PE36136

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE36136-12 = 12 inches long cable
PE36136-100cm = 100 cm long cable

7/16 DIN Male to 7/16 DIN Male Cable 12 Inch Length Using RG225 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to 7/16 DIN Male Cable 12 Inch Length Using RG225 Coax PE36136-12](#)


URL: <https://www.pasternack.com/7-16-male-7-16-male-rg225u-cable-assembly-pe36136-12-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE36136-12 CAD Drawing

7/16 DIN Male to 7/16 DIN Male Cable 12 Inch Length Using RG225 Coax

| REVISIONS | | | |
|-----------|-----------------|----------|----------|
| REV. | DESCRIPTION | DATE | APPROVED |
| A | INITIAL RELEASE | 07/23/19 | SELLIS |



| | |
|---|-----------|
| UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE IN INCHES DIMENSIONS IN [] ARE MILLIMETERS | |
| TOLERANCES: | FRACTIONS |
| X±.2 | [5.08] |
| .XX±.01 | [.25] |
| .XXX±.005 | [.13] |
| ANGLES ± 1° | |
| ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. | |
| THIRD-ANGLE PROJECTION | |

| | |
|---|---------|
| PE PASTERNAK an INFINITI brand | |
| Pasternack Enterprises, Inc. P.O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 www.pasternack.com e-mail: sales@pasternack.com | |
| SIZE | A |
| CAGE | 53919 |
| DRAWN BY | K.DANG |
| PART NUMBER | PE36136 |
| REV | A |

| | |
|--|--------|
| THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION. ALL RIGHTS RESERVED. | |
| SHEET | 1 OF 1 |
| SCALE | N/A |

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.