



1.85mm Male to 1.85mm Male Cable 6 Inch  
Length Using RG405 Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE36523LF-6

**Configuration**

- Connector 1: 1.85mm Male
- Connector 2: 1.85mm Male
- Cable Type: RG405

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		40	GHz
VSWR			1.4:1	

**Specifications by Frequency**

Description	F1	F2	F3	F4	F5	Units
Frequency	2.5	5	20	30	40	GHz
VSWR (Max.)	1.4:1	1.4:1	1.4:1	1.4:1	1.4:1	
Return Loss (Max.)	15.56	15.563	15.563	15.563	15.563	dB

**Mechanical Specifications**

**Cable Assembly**

Length	6 in [152.4 mm]
Diameter	0.312 in [7.92 mm]
Weight	0.031 lbs [14.06 g]

**Cable**

Cable Type	RG405
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	1
Shield Layer 1	Copper

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [1.85mm Male to 1.85mm Male Cable 6 Inch Length Using RG405 Coax, RoHS PE36523LF-6](#)



1.85mm Male to 1.85mm Male Cable 6 Inch  
Length Using RG405 Coax, RoHS

## RF Cable Assemblies Technical Data Sheet

PE36523LF-6

### Connectors

Description	Connector 1	Connector 2
Type	1.85mm Male	1.85mm Male
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Contact Plating Specification	MIL-G-45204, Type II, Class 1	MIL-G-45204, Type II, Class 1
Coupling Nut Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel
Hex Size	5/16 in.	5/16 in.
Torque	8 in-lbs [0.9 Nm]	8 in-lbs [0.9 Nm]
Body Material and Plating	Stainless Steel, Gold	Stainless Steel, Gold
Body Plating Specification	MIL-G-45204, Type II, Class 1	MIL-G-45204, Type II, Class 1

### Compliance Certifications (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant	Yes
REACH Compliant	12/19/2011

### Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [1.85mm Male to 1.85mm Male Cable 6 Inch Length Using RG405 Coax, RoHS PE36523LF-6](#)



## 1.85mm Male to 1.85mm Male Cable 6 Inch Length Using RG405 Coax, RoHS

### RF Cable Assemblies Technical Data Sheet

PE36523LF-6

#### How to Order

Part Number Configuration:

PE36523LF

- xx

uu

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE36523LF-12 = 12 inches long cable  
PE36523LF-100cm = 100 cm long cable

1.85mm Male to 1.85mm Male Cable 6 Inch Length Using RG405 Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [1.85mm Male to 1.85mm Male Cable 6 Inch Length Using RG405 Coax, RoHS PE36523LF-6](http://www.pasternack.com/1.85mm-male-1.85mm-male-rg405u-cable-assembly-pe36523lf-6-p.aspx)

URL: <http://www.pasternack.com/1.85mm-male-1.85mm-male-rg405u-cable-assembly-pe36523lf-6-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE36523LF-6 CAD Drawing

1.85mm Male to 1.85mm Male Cable 6 Inch Length Using RG405 Coax, RoHS



- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
  2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
  3. DIMENSIONS ARE IN INCHES [mm].
  4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $3/8"$ , WHICHEVER IS GREATER.

DWG TITLE

**PE36523LF**

FSCM NO. 53919

CAD FILE 102015

SCALE N/A

SIZE A

2233

**PE PASTERNAK®**  
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623  
Phone: (949) 261-1920 | Fax: (949) 261-7451  
Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)