

1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax




PE36525-60

## **RF Cable Assemblies Technical Data Sheet**

### Configuration

- Connector 1: 1.85mm Male
- Connector 2: 1.85mm Male
- Cable Type: PE-SR405FL



#### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		40	GHz
VSWR			1.5:1	
Return Loss			15.563	dB
Velocity of Propagation		69.5		%
Capacitance		29 [95.14]		pF/ft [pF/m]

#### **Specifications by Frequency**

Description	F1	F2	F3	F4	F5	Units
Frequency	2.5	5	20	30	40	GHz
Insertion Loss (Typ.)	1.933	2.945	6.2			dB

#### **Mechanical Specifications**

Cable Assembly Length* Diameter	60 in [152.4 cm] 0.312 in [7.92 mm]
Weight	0.085 lbs [38.56 g]
Cable Cable Type	PE-SR405FL

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax PE36525-60

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



## 1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax

## **RF Cable Assemblies Technical Data Sheet**

Impedance Inner Conductor Type Inner Conductor Material and Plating Dielectric Type Number of Shields Shield Layer 1 50 Ohms Solid Copper Clad Steel, Silver PTFE 1 Tinned Copper Braid

#### Connectors

Description	Connector 1	Connector 2		
Туре	1.85mm Male	1.85mm Male		
Impedance	50 Ohms	50 Ohms		
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold		
Contact Plating Specification	MIL-G-45204, Type II, Class 1	MIL-G-45204, Type II, Class 1		
Body Material and Plating	Stainless Steel, Gold	Stainless Steel, Gold		
Body Plating Specification	MIL-G-45204, Type II, Class 1	MIL-G-45204, Type II, Class 1		
Coupling Nut Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel		
Hex Size	5/16 in.	5/16 in.		
Torque	8 in-lbs [0.9 Nm]	8 in-lbs [0.9 Nm]		

#### Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm$  3/8", whichever is greater.

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

• Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax PE36525-60

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



PE36525-60



1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax



## **RF** Cable Assemblies Technical Data Sheet

## PE36525-60

# How to Order Part Number Configuration: PE36525 uu - XX - Unit of Measure: cm = Centimeters <blank> = Inches Length **Base Number** PE36525-12 = 12 inches long cable Example: PE36525-100cm = 100 cm long cable 1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax PE36525-60 URL: https://www.pasternack.com/1.85mm-male-1.85mm-male-pe-sr405fl-cable-assembly-pe36525-60-p.aspx The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

PE36525-60 CAD Drawing 1.85mm Male to 1.85mm Male Cable 60 Inch Length Using PE-SR405FL Coax

