

1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS



RF Cable Assemblies Technical Data Sheet

PE36678-60

Configuration

- Connector 1: 1.85mm Male
- Connector 2: 1.85mm Male
- Cable Type: 098 Series

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		65	GHz
VSWR			1.4:1	
Velocity of Propagation		69.5		%
RF Shielding	90			dB
Capacitance		29.4 [96.46]		pF/ft [pF/m]
Operating Voltage (AC)			1,200	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	6	12	24	36	48	GHz
VSWR (Max.)	1.07:1	1.09:1	1.1:1	1.2:1	1.22:1	

Mechanical Specifications

Cable Assembly Length	
Weight	
One Time Minimum E	Bend Radius

Cable

Cable Type Impedance Inner Conductor Type Inner Conductor Material and Plating Dielectric Type Number of Shields Shield Layer 1 Shield Layer 2 60 in [152.4 cm] 0.011 lbs [4.99 g] 0.25 in [6.35 mm]

098 Series 50 Ohms Solid Copper Clad Steel, Silver PTFE 3 Silver Plated Copper Tape Mylar Tape

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS PE36678-60

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS

RF Cable Assemblies Technical Data Sheet

Shield Layer 3 Jacket Material Jacket Diameter Silver Plated Copper Tape FEP 0.098 in [2.49 mm]

Connectors

Description	Connector 1	Connector 2	
Туре	1.85mm Male	1.85mm Male	
Impedance	50 Ohms	50 Ohms	
Contact Material and Plating	Copper Clad Steel, Silver	Copper Clad Steel, Silver	
Dielectric Type	PTFE	PTFE	
Coupling Nut Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel	
Hex Size	5/16 in.	5/16 in.	
Torque	8 in-lbs [0.9 Nm]	8 in-lbs [0.9 Nm]	
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel	

Environmental Specifications

Temperature Operating Range

-48 to +204 deg C

Compliance Certifications (visit www.Pasternack.com for current document) RoHS Compliant Yes

Plotted and Other Data

Notes: • Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS PE36678-60

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com · Techsupport@Pasternack.com



PE36678-60



1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS

RF Cable Assemblies Technical Data Sheet

C TEPLACK

PE36678-60

How to Order Part Number Configuration: **PE36678** uu - XX - Unit of Measure: cm = Centimeters <blank> = Inches Lenath **Base Number** PE36678-12 = 12 inches long cable Example: PE36678-100cm = 100 cm long cable 1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS PE36678-60 URL: http://www.pasternack.com/1.85mm-male-1.85mm-male-095-series-cable-assembly-pe36678-60-p.aspx The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

PE36678-60 CAD Drawing 1.85mm Male to 1.85mm Male Precision Cable 60 Inch Length Using 098 Series Coax, RoHS

