


| COMPONENTS    | IMPEDANCE |
|---------------|-----------|
| BNC FEMALE    | 50 OHM    |
| BNC FEMALE    | 50 OHM    |
| RG59B/U-BLACK | 75 OHM    |
|               |           |

| Standard Lengths |                         |
|------------------|-------------------------|
| -12              | 12"                     |
| -24              | 24"                     |
| -36              | 36"                     |
| -48              | 48"                     |
| -60              | 60"                     |
| -XXX             | Custom Length in inches |
|                  |                         |



**PASTERNAK ENTERPRISES, INC.**  
P.O BOX 16759, IRVINE, CA 92623  
PHONE (949) 261-1920 FAX (949) 261-7451  
  
WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)  
  
**COAXIAL & FIBER OPTICS**

DWG TITLE

**PE3675LF-XX**

DES.

CABLE ASSEMBLY, RG59B/U-BLACK, BNC FEMALE TO BNC FEMALE (LEAD FREE)

REV. A

**FSCM NO. 53919**

CAD FILE

021108

SCALE N/A

SIZE A

127

**NOTES:**

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.
4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $\pm 3/8"$ , WHICHEVER IS GREATER.



**RoHS**  
2002/95/EC

RoHS  
Compliance  
Certified