



3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable  
60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS

TECHNICAL DATA SHEET

PE3930LF-60

**Configuration**

Connector 1	3/4"-20 Twinax Male
Connector 2	3/4"-20 Twinax Male
Cable Type	PE-S330

**Electrical Specifications**

Frequency Range	DC to 400 MHz
Impedance	95 Ohms

**Performance by Frequency**

**Frequency 1**

Frequency	50 MHz
Insertion Loss	0.3 dB

**Frequency 2**

Frequency	100 MHz
Insertion Loss	0.43 dB

**Frequency 3**

Frequency	200 MHz
Insertion Loss	0.66 dB

**Frequency 4**

Frequency	400 MHz
Insertion Loss	0.102 dB

**Mechanical Specifications**

**Size**

Length	60 in [152.4 cm]
Diameter	0.866 in [22 mm]
Weight	0.373 lbs [169.19 g]
Cable Color	Black

**Cable**

Cable Type	PE-S330
Inner Conductor Type	Stranded
Cable Inner Conductor	Copper, Tin
No of Shields	2
Dielectric Type	PE
Jacket Material	PVC
Jacket Diameter	0.33 in [8.38 mm]

**Connector 1**

Type	3/4"-20 Twinax Male
Configuration	Straight

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable 60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS PE3930LF-60](#)



3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable  
60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS

TECHNICAL DATA SHEET

PE3930LF-60

Inner Conductor Material and Plating  
Inner Conductor Plating Specification  
Body Material and Plating  
Body Plating Specification  
Dielectric Type

Brass, Gold  
30μ in. minimum  
Brass, Nickel  
100μ in. minimum  
PBT

**Connector 2**

Type  
Configuration  
Inner Conductor Material and Plating  
Inner Conductor Plating Specification  
Body Material and Plating  
Body Plating Specification  
Dielectric Type

3/4"-20 Twinax Male  
Straight  
Brass, Gold  
30μ in. minimum  
Brass, Nickel  
100μ in. minimum  
PBT

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant

Yes

**Plotted and Other Data**

Notes:

- Values at +25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable 60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS PE3930LF-60](#)



3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable  
60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS

TECHNICAL DATA SHEET

PE3930LF-60

**How to Order**

Part Number Configuration:

**PE3930LF**

**- xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3930LF-12 = 12 inches long cable  
PE3930LF-100cm = 100 cm long cable

3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable 60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable 60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS PE3930LF-60](http://www.pasternack.com/3-4-20-male-3-4-20-male-pe-s330-cable-pe3930lf-60-p.aspx)


URL: <http://www.pasternack.com/3-4-20-male-3-4-20-male-pe-s330-cable-pe3930lf-60-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE3930LF-60 CAD Drawing

3/4 inch-20 Twinax Male to 3/4 inch-20 Twinax Male Cable

60 Inch Length Using 100 Ohm PE-S330 Coax, RoHS



Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)

#### NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $3/8"$ , WHICHEVER IS GREATER.

DWG TITLE

**PE3930LF**

FSCM NO. 53919

CAD FILE

032515

SCALE N/A

SIZE A

2233