

# SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax



# **RF Cable Assemblies Technical Data Sheet**

PE39343H-48

# Configuration

Connector 1: SMA MaleConnector 2: FAKRA PlugCable Type: RG316

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	
Capacitance		32 [104.99]		pF/ft [pF/m]

# **Specifications by Frequency**

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Typ.)	0.64	0.84	1.153	1.72	2.52	dB
VSWR (Max.)	1.4:1	1.4:1	1.4:1	1.4:1	1.4:1	
Return Loss (Max.)	15.56	15.563	15.563	15.563	15.563	dB

### **Mechanical Specifications**

### **Cable Assembly**

 Length\*
 48 in [121.92 cm]

 Diameter
 0.37 in [9.4 mm]

 Weight
 0.058 lbs [26.31 g]

### Cable

Cable TypeRG316Impedance50 OhmsInner Conductor TypeStranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTFE
Number of Shields 1

Shield Layer 1 Silver Plated Copper Braid

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax PE39343H-48





# SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax



# **RF Cable Assemblies Technical Data Sheet**

PE39343H-48

Jacket Material Jacket Diameter FEP, Tan 0.098 in [2.49 mm]

#### **Connectors**

Description	Connector 1	Connector 2	
Туре	SMA Male	FAKRA Plug	
Specification	MIL-STD-348A		
Impedance	50 Ohms	50 Ohms	
Configuration	Straight	Straight	
Contact Material and Plating	Brass, Gold	Phosphor Bronze, Gold	
Contact Plating Specification	30μ in. Minimum		
Dielectric Type	PTFE	Teflon	
Outer Conductor Material and Plating		Brass, Nickel	
Body Material and Plating	Brass, Nickel	Plastic	
Body Plating Specification	100μ in. Minimum		
Coupling Nut Material and Plating	Brass, Nickel		
Coupling Nut Plating Specification	100μ in. Minimum		
Hex Size	5/16 in		
Torque	5 in-lbs [0.57 Nm]		

Mechanical Specification Notes:

Compliance Certifications (see product page for current document)

# **Plotted and Other Data**

Notes:

· Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax PE39343H-48



<sup>\*</sup>All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



# SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax



# **RF Cable Assemblies Technical Data Sheet**

PE39343H-48

### **How to Order**

Example: PE39343H-12 = 12 inches long cable PE39343H-100cm = 100 cm long cable

SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax PE39343H-48

URL: https://www.pasternack.com/sma-male-fakra-plug-rg316u-cable-assembly-pe39343h-48-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



**PE39343H-48 CAD Drawing**SMA Male to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax

