

SMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax



RF Cable Assemblies Technical Data Sheet

PE39346H-48

Configuration

Connector 1: SMA FemaleConnector 2: FAKRA PlugCable Type: RG316

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
VSWR			1.5:1	
Velocity of Propagation		66		%
Capacitance	V	32 [104.99]		pF/ft [pF/m]
Operating Voltage (AC)			250	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Typ.)	0.64	0.84	1.153	1.72	2.52	dB

Mechanical Specifications

Cable Assembly

 Length*
 48 in [121.92 cm]

 Diameter
 0.37 in [9.4 mm]

 Weight
 0.065 lbs [29.48 g]

Cable

Cable TypeRG316Impedance50 OhmsInner Conductor TypeStranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTFE
Number of Shields 1

Shield Layer 1 Silver Plated Copper Braid

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax PE39346H-48





SMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax



RF Cable Assemblies Technical Data Sheet

PE39346H-48

Jacket Material Jacket Diameter FEP, Tan 0.098 in [2.49 mm]

Connectors

Description	Connector 1	Connector 2	
Туре	SMA Female	FAKRA Plug	
Specification	MIL-STD-348		
Impedance	50 Ohms	50 Ohms	
Configuration	Straight	Straight	
Mating Cycles	100		
Contact Material and Plating	Beryllium Copper, Gold	Phosphor Bronze, Gold	
Dielectric Type	Teflon	Teflon	
Outer Conductor Material and Plating		Brass, Nickel	
Body Material and Plating	Brass, Nickel	Plastic	

Mechanical Specification Notes:

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

· Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax PE39346H-48



^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



SMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax



RF Cable Assemblies Technical Data Sheet

PE39346H-48

How to Order



Example: PE39346H-12 = 12 inches long cable PE39346H-100cm = 100 cm long cable

SMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax PE39346H-48

URL: https://www.pasternack.com/sma-female-fakra-plug-rg316u-cable-assembly-pe39346h-48-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE39346H-48 CAD DrawingSMA Female to Violet FAKRA Plug Cable 48 Inch Length Using RG316 Coax

