



## SMA Male Right Angle to SMA Male Right Angle Semi-Flexible Precision Cable Using PE-SR402FL Coax, RoHS

### TECHNICAL DATA SHEET

PE39424

#### Hand Formable SMA Male Right Angle to SMA Male Right Angle Semi-Flexible Precision Cable Using PE-SR402FL Coax, RoHS

Pasternack's formable cable assemblies are hand formable semi-rigid replacements that are an alternative to costly preformed assemblies. The formable semi-rigid cable alternatives are dimensionally and electrically similar to their semi-rigid counterpart and have a tinned-copper-braid outer shield that provides excellent RF shielding. The hand formable cable assemblies from Pasternack do not require special tooling to shape or reshape the assemblies and can replace standard semi-rigid versions. The assemblies are available with or without a PVC jacket and are RoHS compliant,

- Dimensionally and electrically the same as standard, solid outer conductor semi-rigid coax
- Cable may be formed by hand and does not require special tools to bend
- May be formed more than once without damaging the outer conductor
- High RF Shielding >100 dB
- 100% Hi-pot and continuity tested
- 100% VSWR tested to max frequency of assembly
- Standard and custom lengths ship the same day

#### Configuration

Connector 1  
 Connector 2  
 Cable Type

SMA Male Right Angle  
 SMA Male Right Angle  
 PE-SR402FL

#### Electrical Specifications

Frequency Range, GHz  
 Impedance, Ohms  
 Maximum VSWR  
 Velocity of Propagation, %  
 RF Shielding, dB  
 Maximum Operating Voltage, Vrms

DC to 10  
 50  
 1.35:1  
 69  
 100  
 335

#### Typical Electrical Specifications

##### Frequency 1

Frequency, MHz  
 Insertion Loss

1000  
 0.119 dB/ft [ 0.39 dB/m ]

##### Frequency 2

Frequency, GHz  
 Insertion Loss

5  
 0.28 dB/ft [ 0.92 dB/m ]

##### Frequency 3

Frequency, GHz  
 Insertion Loss

10  
 0.421 dB/ft [ 1.38 dB/m ]

Electrical Specification Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to SMA Male Right Angle Semi-Flexible Precision Cable Using PE-SR402FL Coax, RoHS PE39424](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



## SMA Male Right Angle to SMA Male Right Angle Semi-Flexible Precision Cable Using PE-SR402FL Coax, RoHS

### TECHNICAL DATA SHEET

PE39424

#### Mechanical Specifications

##### Cable Assembly

Cable Type PE-SR402FL

##### Temperature

Temperature Operating Range, deg C -55 to +125

Diameter, in [mm] 0.139 [3.53]

Weight, lbs [g] 0.027 [12.25]

One Time Minimum Bend Radius, in [mm] 0.75 [19.05]

Repeated Minimum Bend Radius, in [mm] 1.57 [39.88]

##### Cable

Center Conductor Type Solid

Cable Inner Conductor Copper, Silver

No of Shields 1

Dielectric Type PTFE

##### Connector 1

Type SMA Male Right Angle  
Configuration Right Angle

##### Connector 2

Type SMA Male Right Angle  
Configuration Right Angle

#### Compliance Certifications (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant Yes

#### Plotted and Other Data

Notes: Values at 25 °C, sea level

SMA Male Right Angle to SMA Male Right Angle Semi-Flexible Precision Cable Using PE-SR402FL Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to SMA Male Right Angle Semi-Flexible Precision Cable Using PE-SR402FL Coax, RoHS PE39424](http://www.pasternack.com/sma-male-sma-male-pe-sr402fl-cable-assembly-pe39424-p.aspx)

URL: <http://www.pasternack.com/sma-male-sma-male-pe-sr402fl-cable-assembly-pe39424-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

# PE39424 CAD Drawing

SMA Male Right Angle to SMA Male Right Angle Semi-Flexible  
Precision Cable Using PE-SR402FL Coax, RoHS



Note: This part is lead free.

How To Order					
Part Number Configuration			Examples	Part # Ext.	Length In Inches
PE3 <input type="text" value="zzz"/> <input type="text" value="yy"/> - <input type="text" value="xx"/> <input type="text" value="uu"/>			PE3000LF-100	-12	12"
			PE3000-100	-24	24"
			PE3000LF-100CM	-36	36"
			PE3000-100CM	-48	48"
				-60	60"
				-xx	Custom Length
00 - 99999 LF = Lead Free < Blank > = Standard Note: LF applies only to RF cables					
			CM = Centimeters < Blank > = Inches Length		

- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
  2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
  3. DIMENSIONS ARE IN INCHES [mm].
  4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $3/8"$ , WHICHEVER IS GREATER.

DWG TITLE  
**PE39424**

**PASTERNAK ENTERPRISES, INC.**  
 P.O. BOX 16759, IRVINE, CA 92623  
 PHONE (949) 261-1920 FAX (949) 261-7451  
 WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
 E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)  
**COAXIAL & FIBER OPTICS**



2231

SIZE A

SCALE N/A

CAD FILE 041912

FSCM NO. 53919

REV. -