



N Male Right Angle to N Male Right Angle Semi-Flexible Precision Cable 9 Inch Length Using PE-SR402FL Coax, RoHS

TECHNICAL DATA SHEET

PE39452-9

Hand Formable N Male Right Angle to N Male Right Angle Semi-Flexible Precision Cable 9 Inch Length Using PE-SR402FL Coax, RoHS

Pasternack's formable cable assemblies are hand formable semi-rigid replacements that are an alternative to costly preformed assemblies. The formable semi-rigid cable alternatives are dimensionally and electrically similar to their semi-rigid counterpart and have a tinned-copper-braid outer shield that provides excellent RF shielding. The hand formable cable assemblies from Pasternack do not require special tooling to shape or reshape the assemblies and can replace standard semi-rigid versions. The assemblies are available with or without a PVC jacket and are RoHS compliant,

- Dimensionally and electrically the same as standard, solid outer conductor semi-rigid coax
- Cable may be formed by hand and does not require special tools to bend
- May be formed more than once without damaging the outer conductor
- High RF Shielding >100 dB
- 100% Hi-pot and continuity tested
- 100% VSWR tested to max frequency of assembly
- Standard and custom lengths ship the same day

Configuration

Connector 1
 Connector 2
 Cable Type

N Male Right Angle
 N Male Right Angle
 PE-SR402FL

Electrical Specifications

Frequency Range, GHz
 Impedance, Ohms
 Maximum VSWR
 Velocity of Propagation, %
 RF Shielding, dB
 Maximum Operating Voltage, Vrms

DC to 11
 50
 1.5:1
 69
 100
 350

Typical Electrical Specifications

Frequency 1

Frequency, MHz
 Insertion Loss

1000
 0.119 dB/ft [0.39 dB/m]

Frequency 2

Frequency, GHz
 Insertion Loss

5
 0.28 dB/ft [0.92 dB/m]

Frequency 3

Frequency, GHz
 Insertion Loss

10
 0.421 dB/ft [1.38 dB/m]

Electrical Specification Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male Right Angle to N Male Right Angle Semi-Flexible Precision Cable 9 Inch Length Using PE-SR402FL Coax, RoHS PE39452-9](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



N Male Right Angle to N Male Right Angle Semi-Flexible
Precision Cable 9 Inch Length Using PE-SR402FL Coax, RoHS

TECHNICAL DATA SHEET

PE39452-9

Mechanical Specifications

Cable Assembly

Cable Type PE-SR402FL

Temperature

Temperature Operating Range, deg C -55 to +125

Size

Length, in [mm] 9 [228.6]

Diameter, in [mm] 0.139 [3.53]

Weight, lbs [g] 0.027 [12.25]

One Time Minimum Bend Radius, in [mm] 0.75 [19.05]

Repeated Minimum Bend Radius, in [mm] 1.57 [39.88]

Cable

Center Conductor Type Solid

Cable Inner Conductor Copper, Silver

No of Shields 1

Dielectric Type PTFE

Connector 1

Type N Male Right Angle

Configuration Right Angle

Connector 2

Type N Male Right Angle

Configuration Right Angle

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

N Male Right Angle to N Male Right Angle Semi-Flexible Precision Cable 9 Inch Length Using PE-SR402FL Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male Right Angle to N Male Right Angle Semi-Flexible Precision Cable 9 Inch Length Using PE-SR402FL Coax, RoHS PE39452-9](http://www.pasternack.com/n-male-n-male-pe-sr402fl-cable-assembly-pe39452-9-p.aspx)

URL: <http://www.pasternack.com/n-male-n-male-pe-sr402fl-cable-assembly-pe39452-9-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE39452-9 CAD Drawing

N Male Right Angle to N Male Right Angle Semi-Flexible Precision
Cable 9 Inch Length Using PE-SR402FL Coax, RoHS



Note: This part is lead free.

How To Order					
Part Number Configuration PE3 - 00 - 99999 LF = Lead Free < Blank > = Standard Note: LF applies only to RF cables	Examples PE3000LF-100 PE3000-100 PE3000LF-100CM PE3000-100CM	Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
		-12	12"	-25CM	25Cm
		-24	24"	-50CM	50Cm
		-36	36"	-75CM	75Cm
		-48	48"	-100CM	100Cm
		-60	60"	-125CM	125Cm
CM = Centimeters < Blank > = Inches Length		-xx	Custom Length	-xxCM	Custom Length



PASTERNAK ENTERPRISES, INC.
 P.O. BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

DWG TITLE

PE39452

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].
 4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

2231

SIZE A

SCALE N/A

CAD FILE 041912

FSCM NO. 53919

REV. -