



SMA Female to SMA Female Cable 36 Inch Length Using LMR-100 Coax

TECHNICAL DATA SHEET

PE3C0045-36

SMA Female to SMA Female Cable 36 Inch Length Using LMR-100 Coax

Configuration

Connector 1	SMA Female
Connector 1 Specification	MIL-STD-348
Connector 2	SMA Female
Connector 2 Specification	MIL-STD-348
Cable Type	LMR-100A
Impedance, Ohms	50

Mechanical Specifications

Cable Assembly

Cable Type	LMR-100A
------------	----------

Temperature

Temperature Operating Range, deg C	-40 to +85
Temperature Storage Range, deg C	-70 to +85

Size

Length, in [mm]	36 [914.4]
Diameter, in [mm]	0.312 [7.92]
Weight, lbs [g]	0.04 [18.14]
Cable Color	Black
One Time Minimum Bend Radius, in [mm]	0.25 [6.35]
Repeated Minimum Bend Radius, in [mm]	1 [25.4]

Cable

No of Shields	2
Dielectric Type	PE
Jacket Material	PVC
Jacket Diameter, in [mm]	0.11 [2.79]

Connector 1

Type	SMA Female
Configuration	Straight
Mating Cycles	100
Inner Conductor Material and Plating	Beryllium Copper, Gold
Body Material and Plating	Brass, Nickel
Dielectric Type	Teflon

Connector 2

Type	SMA Female
Configuration	Straight
Mating Cycles	100

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to SMA Female Cable 36 Inch Length Using LMR-100 Coax PE3C0045-36](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Female to SMA Female Cable 36 Inch
Length Using LMR-100 Coax

TECHNICAL DATA SHEET

PE3C0045-36

Inner Conductor Material and Plating
Body Material and Plating
Dielectric Type

Beryllium Copper, Gold
Brass, Nickel
Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes:


Values at 25 °C, sea level

SMA Female to SMA Female Cable 36 Inch Length Using LMR-100 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to SMA Female Cable 36 Inch Length Using LMR-100 Coax PE3C0045-36](http://www.pasternack.com/sma-female-sma-female-lmr100-cable-assembly-pe3c0045-36-p.aspx)

URL: <http://www.pasternack.com/sma-female-sma-female-lmr100-cable-assembly-pe3c0045-36-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



How To Order					
Part Number Configuration		Examples			
PE3 [zzz] [yy] - [xx] [uu]		PE3000LF-100		-12	
		PE3000-100		-24	
		PE3000LF-100CM		-36	
		PE3000-100CM		-48	
				-60	
				-xx	
00 - 99999					
LF = RoHS Compliant					
< Blank > = Standard					
Note: LF applies only to RF cables					

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

**PASTERNAK®**
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

DWG TITLE
PE3C0045

FSCM NO. 53919

CAD FILE 013113

SCALE N/A

SIZE A

2233