



SMA Female 4 Hole Flange to MMCX Plug Right Angle
 Cable 12 Inch Length Using LMR-100 Coax

TECHNICAL DATA SHEET

PE3C0064-12

SMA Female 4 Hole Flange to MMCX Plug Right Angle Cable 12 Inch Length Using LMR-100 Coax

Configuration

Connector 1	SMA Female 4 Hole Flange
Connector 1 Specification	MIL-C-39012
Connector 2	MMCX Plug Right Angle
Connector 2 Specification	BS EN 122340
Cable Type	LMR-100A
Impedance, Ohms	50

Mechanical Specifications

Cable Assembly

Cable Type	LMR-100A
------------	----------

Temperature

Temperature Operating Range, deg C	-40 to +85
Temperature Storage Range, deg C	-70 to +85

Size

Length, in [mm]	12 [304.8]
Diameter, in [mm]	0.5 [12.7]
Weight, lbs [g]	0.04 [18.14]
Cable Color	Black
One Time Minimum Bend Radius, in [mm]	0.25 [6.35]
Repeated Minimum Bend Radius, in [mm]	1 [25.4]

Cable

No of Shields	2
Dielectric Type	PE
Jacket Material	PVC
Jacket Diameter, in [mm]	0.11 [2.79]

Connector 1

Type	SMA Female 4 Hole Flange
Configuration	Straight
Mount Method	4 Hole Flange
Inner Conductor Material and Plating	Gold
Inner Conductor Plating Specification	MIL-G-45204
Body Material and Plating	Brass, Nickel
Dielectric Type	Teflon

Connector 2

Type	MMCX Plug Right Angle
Configuration	Right Angle

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female 4 Hole Flange to MMCX Plug Right Angle Cable 12 Inch Length Using LMR-100 Coax PE3C0064-12](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.





SMA Female 4 Hole Flange to MMCX Plug Right Angle
Cable 12 Inch Length Using LMR-100 Coax

TECHNICAL DATA SHEET

PE3C0064-12

Inner Conductor Material and Plating	Brass, Gold
Inner Conductor Plating Specification	30 μ in. minimum
Body Material and Plating	Brass, Gold
Body Plating Specification	3 μ in. minimum
Dielectric Type	Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes:

Values at 25 °C, sea level


SMA Female 4 Hole Flange to MMCX Plug Right Angle Cable 12 Inch Length Using LMR-100 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female 4 Hole Flange to MMCX Plug Right Angle Cable 12 Inch Length Using LMR-100 Coax PE3C0064-12](http://www.pasternack.com/sma-female-mmcx-plug-lmr100-cable-assembly-pe3c0064-12-p.aspx)

URL: <http://www.pasternack.com/sma-female-mmcx-plug-lmr100-cable-assembly-pe3c0064-12-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE3C0064-12 CAD Drawing
 SMA Female 4 Hole Flange to MMCX Plug Right Angle
 Cable 12 Inch Length Using LMR-100 Coax



How To Order		Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
Part Number Configuration PE3 [zzz] [yy] - [xx] [uu] 00 - 99999 LF = RoHS Compliant < Blank > = Standard Note: LF applies only to RF cables		-12	12"	-25CM	25Cm
Examples PE3000LF-100 PE3000-100 PE3000LF-100CM PE3000-100CM CM = Centimeters < Blank > = Inches Length		-24	24"	-50CM	50Cm
		-36	36"	-75CM	75Cm
		-48	48"	-100CM	100Cm
		-60	60"	-125CM	125Cm
		-xx	Custom Length	-xxCM	Custom Length

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].
 4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.

DWG TITLE
PE3C0064

PE PASTERNAK
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919	CAD FILE 020513	SCALE N/A	SIZE A	2233
----------------	-----------------	-----------	--------	------