



N Male to N Male With Times Connectors Cable 36 Inch Length Using LMR-600 Coax

TECHNICAL DATA SHEET

PE3C0110-36

N Male to N Male With Times Connectors Cable 36 Inch Length Using LMR-600 Coax

Configuration

Connector 1	N Male
Connector 2	N Male
Cable Type	LMR-600
Impedance, Ohms	50

Mechanical Specifications

Cable Assembly

Cable Type	LMR-600
------------	---------

Temperature

Temperature Operating Range, deg C	-40 to +85
Temperature Storage Range, deg C	-70 to +85

Size

Length, in [mm]	36 [914.4]
Diameter, in [mm]	1 [25.4]
Weight, lbs [g]	0.486 [220.45]
Cable Color	Black
One Time Minimum Bend Radius, in [mm]	1.5 [38.1]
Repeated Minimum Bend Radius, in [mm]	6 [152.4]

Cable

No of Shields	2
Dielectric Type	PE (F)
Jacket Material	PE
Jacket Diameter, in [mm]	0.59 [14.99]

Connector 1

Type	N Male
Configuration	Straight
Inner Conductor Material and Plating	Beryllium Copper, Gold
Inner Conductor Plating Specification	1.27µm minimum
Coupling Nut Material and Plating	Brass, Tri-Metal
Coupling Nut Plating Specification	2µm minimum
Hex Size, mm	20.57
Torque, in-lbs [Nm]	44 [4.97]
Body Material and Plating	Brass, Tri-Metal
Body Plating Specification	2µm minimum
Dielectric Type	PTFE

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male With Times Connectors Cable 36 Inch Length Using LMR-600 Coax PE3C0110-36](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



N Male to N Male With Times Connectors Cable
36 Inch Length Using LMR-600 Coax

TECHNICAL DATA SHEET

PE3C0110-36

Connector 2

Type	N Male
Configuration	Straight
Inner Conductor Material and Plating	Beryllium Copper, Gold
Inner Conductor Plating Specification	1.27µm minimum
Coupling Nut Material and Plating	Brass, Tri-Metal
Coupling Nut Plating Specification	2µm minimum
Hex Size, mm	20.57
Torque, in-lbs [Nm]	44 [4.97]
Body Material and Plating	Brass, Tri-Metal
Body Plating Specification	2µm minimum
Dielectric Type	PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes:

Values at 25 °C, sea level

N Male to N Male With Times Connectors Cable 36 Inch Length Using LMR-600 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male With Times Connectors Cable 36 Inch Length Using LMR-600 Coax PE3C0110-36](http://www.pasternack.com/n-male-n-male-lmr600-cable-assembly-pe3c0110-36-p.aspx)

URL: <http://www.pasternack.com/n-male-n-male-lmr600-cable-assembly-pe3c0110-36-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE3C0110-36 CAD Drawing

N Male to N Male With Times Connectors Cable 36 Inch Length Using LMR-600 Coax



How To Order				Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
Part Number Configuration		Examples		-12	12"	-25CM	25Cm
PE3	zzz	yy	- xx uu	-24	24"	-50CM	50Cm
00 - 99999	LF = RoHS Compliant			-36	36"	-75CM	75Cm
< Blank > = Standard			CM = Centimeters		-48	48"	100Cm
Note: LF applies only to RF cables			< Blank > = Inches		-60	60"	125Cm
			Length		-xx	Custom Length	Custom Length

- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].
 4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

DWG TITLE
PE3C0110

PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919

CAD FILE 022613

SCALE N/A

SIZE A

2233