

SMA Male to SMA Male Low Loss Cable 72 Inch Length Using PE-P142LL Coax with HeatShrink



PE-P142LL

0.195 (FEP) ) (Stainless Steel)

0.320 (Stainless

# **RF Cable Assemblies Technical Data Sheet**

#### Configuration

- Connector 1: SMA Male
- Connector 2: SMA Male
- Cable Type: PE-P142LL

#### Features

- Passivated Stainless Steel Flexible Armoring
- Type N Male to N Male and SMA Male to SMA Male Configurations Available
- Robust Connector/Armor Interface
- Triple Shielded Low Loss PE-P142LL Coax with Expanded PTFE Tape Dielectric
- Standard inch lengths: 12", 24", 36", 48", 60", 72", 120"
- Standard metric lengths: 50cm, 100cm, 150cm, 200cm
- SMA rated to 20 GHz with a 1.35:1 VSWR
- N type rated to 18 GHz with a 1.35:1 VSWR
- · Custom lengths available, call for pricing and lead time

### **Applications**

- General Purpose
- Laboratory Use

#### Description

Pasternack's new SMA and type N armored test cables utilize a flexible passivated stainless steel armoring that is designed to handle harsh industrial environments, common in production test systems. Its rugged armoring is very flexible and ensures RF signal integrity during test, even when exposed to a high traffic production environment. These armored RF test cables are equipped with passivated stainless steel connectors, with the SMA designed to operate to 20 GHz and the type N to 18 GHz. A robust mechanical connector/armoring interface increases the durability of the test cables, and its strain relief boot increases the life of the test cable. Pasternack's armored test cables are built using PE-P142LL coaxial cable that is triple shielded with an expanded PTFE dielectric, guaranteeing low loss performance.

#### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		20	GHz
VSWR		1.25:1	1.35:1	
Velocity of Propagation		80		%

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Low Loss Cable 72 Inch Length Using PE-P142LL Coax with Heat-Shrink PE3C0230-72

ISO 9001 : 2008 Registered

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

## PE3C0230-72

OUTER SHIELD

MIDDLE SHIELD

DIELECTRIC

INNER SHIELD

SOLID CENTER

CONDUCTOR

JACKET



SMA Male to SMA Male Low Loss Cable 72 Inch Length Using PE-P142LL Coax with HeatShrink

# **RF Cable Assemblies Technical Data Sheet**

Specifications by Frequency



## PE3C0230-72

#### F4 Description **F1 F2** F3 F5 Units 3 5 10 18 GHz Frequency 1 Insertion Loss (Typ.) 0.48 0.84 1.5 2.16 dB 1.08 Power Handling (Max.) 220 Watts **Electrical Specification Notes:** Insertion loss does not include the loss of the connectors. Insertion loss is estimated as 0.05 x sqrt(fGHz) dB per connector. **Mechanical Specifications Cable Assembly** Length\* 72 in [182.88 cm] Weight 0.659 lbs [298.92 g] Cable PE-P142LL Cable Type Impedance 50 Ohms Inner Conductor Type Solid Inner Conductor Material and Plating Copper, Silver **Dielectric Type** PTFE Number of Shields 3 Shield Layer 1 Silver Plated Copper Braid Shield Layer 2 Aluminum Polyester Shield Layer 3 Silver Plated Copper Braid Jacket Material Passivated Stainless Steel Jacket Diameter 0.32 in [8.13 mm] Repeated Minimum Bend Radius 1 in [25.4 mm]

Connectors
------------

Description	Connector 1	Connector 2
Туре	SMA Male	SMA Male
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel
Coupling Nut Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel

Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Low Loss Cable 72 Inch Length Using PE-P142LL Coax with Heat-Shrink PE3C0230-72

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com







SMA Male to SMA Male Low Loss Cable 72 Inch Length Using PE-P142LL Coax with HeatShrink

Accomplies Technical D



r cable Assemblies rechnical i	
Environmental Specifications Temperature Operating Range	-55 to +200 deg C
Compliance Certifications (see prod	uct page for current document)
Plotted and Other Data Notes: • Values at 25°C, sea level.	
How to Order	
Part Number Configuration:	PE3C0230 - xx uu Unit of Measure: cm = Centimeters <blank> = Inches Length Base Number</blank>
Example: PE3C0230-12 = 12 inc PE3C0230-100cm = 10	

SMA Male to SMA Male Low Loss Cable 72 Inch Length Using PE-P142LL Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMA Male Low Loss Cable 72 Inch Length Using PE-P142LL Coax with HeatShrink PE3C0230-72

URL: https://www.pasternack.com/sma-male-sma-male-pe-p142ll-cable-assembly-pe3c0230-72-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451





PE3C0230-72 CAD Drawing SMA Male to SMA Male Low Loss Cable 72 Inch Length

MA Male to SMA Male Low Loss Cable 72 Inch Lengi Using PE-P142LL Coax with HeatShrink

