



## N Male Right Angle to N Female Bulkhead Low Loss Test Cable 60 Inch Length Using PE-P300LL Coax, RoHS

### RF Cable Assemblies Technical Data Sheet

**PE3C2953-60**

#### Configuration

- Connector 1: N Male Right Angle
- Connector 2: N Female Bulkhead
- Cable Type: PE-P300LL

#### Features

- 83% Velocity of Propagation
- Shielding effectiveness > 95 dB
- Maximum VSWR is < 1.40:1 to 18 GHz
- Minimum Bend Radius of 1.5 inches
- Operating Temperature range of -55 to +125 °C
- ROHS and REACH Compliant
- Same day shipment of custom lengths
- 100% Continuity and RF tested



#### Description

The PE3C2953 high performance test cable's 0.3 inch diameter and 83% phase velocity offer very low loss performance up to 18 GHz. The durable stainless steel connectors and FEP jacket provide a cost effective design ideal for test environments where a rugged cable assembly is required. The series is offered with Type N, TNC, and SMA connectors all rated to 18 GHz. A heavy Duty boot provides improved strain relief and adds to the durability of the cable assemblies. These cable assemblies are built using a double shielded flexible cable, providing excellent shielding effectiveness of greater than 95 dB. All PE3C2953 cable assemblies are 100% Continuity and RF tested to published specifications. Custom lengths are built to order and shipped same day.

#### Electrical Specifications

| Description             | Minimum | Typical    | Maximum | Units        |
|-------------------------|---------|------------|---------|--------------|
| Frequency Range         | DC      |            | 18      | GHz          |
| VSWR                    |         |            | 1.4:1   |              |
| Velocity of Propagation |         | 83         |         | %            |
| RF Shielding            | 95      |            |         | dB           |
| Capacitance             |         | 25 [82.02] |         | pF/ft [pF/m] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male Right Angle to N Female Bulkhead Low Loss Test Cable 60 Inch Length Using PE-P300LL Coax, RoHS PE3C2953-60](#)



N Male Right Angle to N Female Bulkhead Low Loss Test  
Cable 60 Inch Length Using PE-P300LL Coax, RoHS

## RF Cable Assemblies Technical Data Sheet

**PE3C2953-60**

### Specifications by Frequency

| Description           | F1    | F2    | F3  | F4   | F5  | Units |
|-----------------------|-------|-------|-----|------|-----|-------|
| Frequency             | 1     | 2     | 4.5 | 9    | 18  | GHz   |
| Insertion Loss (Max.) | 0.5   | 0.6   | 0.8 | 1.1  | 1.5 | dB    |
| Insertion Loss (Typ.) | 0.45  | 0.55  | 0.7 | 0.95 | 1.3 | dB    |
| Power Handling (Max.) | 1,800 | 1,200 | 900 | 650  | 400 | Watts |

### Mechanical Specifications

#### Cable Assembly

|          |                     |
|----------|---------------------|
| Length*  | 60 in [152.4 cm]    |
| Diameter | 0.875 in [22.23 mm] |

#### Cable

|                                      |                           |
|--------------------------------------|---------------------------|
| Cable Type                           | PE-P300LL                 |
| Impedance                            | 50 Ohms                   |
| Inner Conductor Type                 | Solid                     |
| Inner Conductor Material and Plating | Copper, Silver            |
| Dielectric Type                      | PTFE                      |
| Number of Shields                    | 3                         |
| Shield Layer 1                       | Silver Plated Copper Tape |
| Shield Layer 2                       | Aluminum Polyester        |
| Shield Layer 3                       | Silver Plated Copper Wire |
| Jacket Material                      | FEP, Green                |
| Jacket Diameter                      | 0.3 in [7.62 mm]          |
| Repeated Minimum Bend Radius         | 1.5 in [38.1 mm]          |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male Right Angle to N Female Bulkhead Low Loss Test Cable 60 Inch Length Using PE-P300LL Coax, RoHS PE3C2953-60](#)



N Male Right Angle to N Female Bulkhead Low Loss Test  
Cable 60 Inch Length Using PE-P300LL Coax, RoHS

## RF Cable Assemblies Technical Data Sheet

**PE3C2953-60**

### Connectors

| Description                           | Connector 1                | Connector 2                        |
|---------------------------------------|----------------------------|------------------------------------|
| Type                                  | N Male Right Angle         | N Female Bulkhead                  |
| Specification                         |                            | MIL-STD-348                        |
| Impedance                             | 50 Ohms                    | 50 Ohms                            |
| Mating Cycles                         |                            | 500                                |
| Contact Material and Plating          | Beryllium Copper, Gold     | Beryllium Copper, Gold over Nickel |
| Contact Plating Specification         | ASTM-B488                  | 50 µin minimum                     |
| Dielectric Type                       | PTFE                       | PEI                                |
| Outer Conductor Material and Plating  |                            | Passivated Stainless Steel         |
| Outer Conductor Plating Specification |                            | SAE-AMS-2700                       |
| Coupling Nut Material and Plating     | Passivated Stainless Steel |                                    |
| Coupling Nut Plating Specification    | SAE-AMS-2700               |                                    |
| Torque                                |                            | 20 in-lbs [2.26 Nm]                |
| Body Material and Plating             | Passivated Stainless Steel | Passivated Stainless Steel         |
| Body Plating Specification            | SAE-AMS-2700               | SAE-AMS-2700                       |

Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8"$ , whichever is greater.

### Environmental Specifications

#### Temperature

Operating Range -55 to +125 deg C

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male Right Angle to N Female Bulkhead Low Loss Test Cable 60 Inch Length Using PE-P300LL Coax, RoHS PE3C2953-60](#)



N Male Right Angle to N Female Bulkhead Low Loss Test  
Cable 60 Inch Length Using PE-P300LL Coax, RoHS

## RF Cable Assemblies Technical Data Sheet

**PE3C2953-60**

### How to Order

Part Number Configuration:

**PE3C2953**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3C2953-12 = 12 inches long cable  
PE3C2953-100cm = 100 cm long cable

N Male Right Angle to N Female Bulkhead Low Loss Test Cable 60 Inch Length Using PE-P300LL Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male Right Angle to N Female Bulkhead Low Loss Test Cable 60 Inch Length Using PE-P300LL Coax, RoHS PE3C2953-60](https://www.pasternack.com/n-male-n-female-pe-p300ll-cable-assembly-pe3c2953-60-p.aspx)

URL: <https://www.pasternack.com/n-male-n-female-pe-p300ll-cable-assembly-pe3c2953-60-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C2953-60 CAD Drawing

N Male Right Angle to N Female Bulkhead Low Loss Test Cable  
60 Inch Length Using PE-P300LL Coax, RoHS



NOTE:  
LABEL FOR CABLE LENGTHS 48" OR SHORTER TO BE CENTERED. 48" OR LONGER WILL BE 12" AWAY FROM CONNECTOR.

- NOTES:
- 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
  - 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
  - 3. DIMENSIONS ARE IN INCHES [mm].
  - 4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $3/8"$ , WHICHEVER IS GREATER.

|           |  |                |  |          |       |      |      |
|-----------|--|----------------|--|----------|-------|------|------|
| DWG TITLE |  | FSCM NO. 53919 |  | CAD FILE | SCALE | SIZE |      |
| PE3C2953  |  |                |  | 062116   | N/A   | A    | 2233 |

**PASTERNAK**  
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451  
Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)