



BNC Male to Straight Cut Lead Cable 60 Inch Length Using RG188 Coax

RF Cable Assemblies Technical Data Sheet

PE3C3583-60

Configuration

- Connector 1: BNC Male
- Connector 2: Straight Cut Lead
- Cable Type: RG188

Features

- PTFE Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C3583-60 50 ohm BNC male to straight cut lead 60 inch cable using RG188 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Mechanical Specifications

Cable Assembly

Length* 60 in [152.4 cm]

Cable

| | |
|--------------------------------------|----------------------------|
| Cable Type | RG188 |
| Impedance | 50 Ohms |
| Inner Conductor Type | Stranded |
| Inner Conductor Material and Plating | Copper Clad Steel, Silver |
| Dielectric Type | PTFE |
| Number of Shields | 1 |
| Shield Layer 1 | Silver Plated Copper Braid |
| Jacket Material | PTFE, White |
| Jacket Diameter | 0.11 in [2.79 mm] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to Straight Cut Lead Cable 60 Inch Length Using RG188 Coax PE3C3583-60](#)



BNC Male to Straight Cut Lead Cable 60 Inch Length Using RG188 Coax

RF Cable Assemblies Technical Data Sheet

PE3C3583-60

Connectors

| Description | Connector 1 | Connector 2 |
|------------------------------------|------------------|-------------------|
| Type | BNC Male | Straight Cut Lead |
| Specification | MIL-STD-348A | |
| Impedance | 50 Ohms | 0 Ohms |
| Contact Material and Plating | Brass, Gold | |
| Contact Plating Specification | 50µ in. minimum | |
| Dielectric Type | Teflon | |
| Body Material and Plating | Brass, Nickel | |
| Body Plating Specification | 100µ in. minimum | |
| Coupling Nut Material and Plating | Brass, Nickel | |
| Coupling Nut Plating Specification | 100µ in. minimum | |

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Environmental Specifications

Temperature

Operating Range -55 to +165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to Straight Cut Lead Cable 60 Inch Length Using RG188 Coax PE3C3583-60](#)



**BNC Male to Straight Cut Lead Cable
60 Inch Length Using RG188 Coax**

RF Cable Assemblies Technical Data Sheet

PE3C3583-60

How to Order

Part Number Configuration:

PE3C3583

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C3583-12 = 12 inches long cable
PE3C3583-100cm = 100 cm long cable

BNC Male to Straight Cut Lead Cable 60 Inch Length Using RG188 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to Straight Cut Lead Cable 60 Inch Length Using RG188 Coax PE3C3583-60](#)

URL: <https://www.pasternack.com/bnc-male-straight-cut-sexless-rg188au-cable-assembly-pe3c3583-60-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C3583-60 CAD Drawing

BNC Male to Straight Cut Lead Cable 60 Inch Length Using RG188 Coax



BNC MALE

STANDARD TOLERANCES

- .X ±0.2
- .XX ±0.01
- .XXX ±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES



Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

DWG TITLE

PE3C3583

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

CAGE CODE 53919

CAD FILE 09/19/18

SCALE N/A

SIZE A

CN2245