



SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax

RF Cable Assemblies Technical Data Sheet

PE3C4801

Configuration

- Connector 1: SSMB Plug Right Angle
- Connector 2: SSMB Plug Right Angle
- Cable Type: RG178

Features

- Max Frequency 3 GHz
- 70% Phase Velocity
- FEP Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C4801 SSMB plug right angle to SSMB plug right angle cable using RG178 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SSMB to SSMB cable assembly has a plug to plug gender configuration with 50 ohm flexible RG178 coax. The PE3C4801 SSMB plug to SSMB plug cable assembly operates to 3 GHz. The right angle SSMB interfaces on the RG178 cable allow for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.5:1	
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax PE3C4801](#)



SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax

RF Cable Assemblies Technical Data Sheet

PE3C4801

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	3	GHz
Insertion Loss (Max.)	0.21	0.31	0.44	0.7	0.78	dB/ft
	0.69	1.02	1.44	2.3	2.56	dB/m

Electrical Specification Notes:

Insertion Loss data does not include the loss of the connectors. Insertion Loss is estimated as 0.4dB connector loss.

Mechanical Specifications

Cable Assembly

Diameter 0.33 in [8.38 mm]

Cable

Cable Type RG178
 Impedance 50 Ohms
 Inner Conductor Type Stranded
 Inner Conductor Material and Plating Copper Clad Steel, Silver
 Dielectric Type PTFE
 Number of Shields 1
 Shield Layer 1 Silver Plated Copper Braid
 Jacket Material FEP, Tan
 Jacket Diameter 0.072 in [1.83 mm]

Repeated Minimum Bend Radius 0.4 in [10.16 mm]

Connectors

Description	Connector 1	Connector 2
Type	SSMB Plug Right Angle	SSMB Plug Right Angle
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Contact Plating Specification	MIL-G-45204	MIL-G-45204
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Gold	Brass, Gold
Body Plating Specification	MIL-G-45204	MIL-G-45204
Coupling Nut Material and Plating	Brass, Gold	Brass, Gold
Coupling Nut Plating Specification	MIL-G-45204	MIL-G-45204

Mechanical Specification Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax PE3C4801](#)



SSMB Plug Right Angle to SSMB Plug
Right Angle Cable Using RG178 Coax

RF Cable Assemblies Technical Data Sheet

PE3C4801


*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8$ ", whichever is greater.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax PE3C4801](#)



SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax

RF Cable Assemblies Technical Data Sheet

PE3C4801

How to Order

Part Number Configuration:

PE3C4801

- **xx**

uu

Unit of Measure:

cm = Centimeters

<blank> = Inches

Length

Base Number

Example: PE3C4801-12 = 12 inches long cable
PE3C4801-100cm = 100 cm long cable

SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax PE3C4801](#)

URL: <https://www.pasternack.com/ssmb-plug-ssmb-plug-rg178bu-cable-assembly-pe3c4801-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C4801 CAD Drawing

SSMB Plug Right Angle to SSMB Plug Right Angle Cable Using RG178 Coax



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.01
.XXX	±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
 PE3C4801

CAGE CODE
 53919

CAD FILE
 10/16/18

SCALE
 N/A

SIZE
 A

CN2245

PASTERNAK
 THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com