



SMA Female to Snap-On MMBX Plug Cable
100 CM Length Using PE-SR405FLJ Coax

RF Cable Assemblies Technical Data Sheet

PE3C5568/HS-100CM

Configuration

- Connector 1: SMA Female
- Connector 2: Snap-On MMBX Plug
- Cable Type: PE-SR405FLJ

Features

- Max Frequency 12.5 GHz
- Shielding Effectivity > 100 dB
- 69.5% Phase Velocity
- FEP Jacket


Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C5568/HS-100CM SMA female to MMBX plug snap-on 100 cm cable using PE-SR405FLJ coax is part of our full line of RF components available for same-day shipping. Pasternack's formable RF cable assemblies provide an alternative to costly pre-formed semi-rigid assemblies since they are hand formable. This Pasternack SMA to MMBX cable assembly has a female to plug gender configuration with 50 ohm formable PE-SR405FLJ coax. The PE3C5568/HS-100CM SMA female to MMBX plug cable assembly operates to 12.5 GHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to Snap-On MMBX Plug Cable 100 CM Length Using PE-SR405FLJ Coax PE3C5568/HS-100CM](#)



SMA Female to Snap-On MMBX Plug Cable 100 CM Length Using PE-SR405FLJ Coax

RF Cable Assemblies Technical Data Sheet

PE3C5568/HS-100CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.5	GHz
Velocity of Propagation		69.5		%
RF Shielding	100			dB
Group Delay		1.43 [4.69]		ns/ft [ns/m]
Capacitance		29 [95.14]		pF/ft [pF/m]
DC Resistance Inner Conductor		65.7 [215.55]		Ω /1000ft [Ω /Km]
DC Resistance Outer Conductor		10.2 [33.46]		Ω /1000ft [Ω /Km]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.5	1	2.5	5	12.5	GHz
Insertion Loss (Typ.)	0.69	0.93	1.33	2	3.18	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

Mechanical Specifications

Cable Assembly

Length*	39.37 in [100 cm]
Diameter	0.25 in [6.35 mm]

Cable

Cable Type	PE-SR405FLJ
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	1
Outer Conductor Material and Plating	Tinned Copper Composite Braid
Jacket Material	FEP, Black
Jacket Diameter	0.105 in [2.67 mm]
One Time Minimum Bend Radius	0.5 in [12.7 mm]
Repeated Minimum Bend Radius	0.787 in [19.99 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to Snap-On MMBX Plug Cable 100 CM Length Using PE-SR405FLJ Coax PE3C5568/HS-100CM](#)



SMA Female to Snap-On MMBX Plug Cable
100 CM Length Using PE-SR405FLJ Coax

RF Cable Assemblies Technical Data Sheet

PE3C5568/HS-100CM

Connectors

Description	Connector 1	Connector 2
Type	SMA Female	MMBX Plug
Specification	MIL-STD-348	
Impedance	50 Ohms	50 Ohms
Connection Method		Snap-On
Mating Cycles		100
Contact Material and Plating	Gold	Beryllium Copper, Gold
Contact Plating Specification	MIL-G-45204	
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating		Brass, Gold
Body Material and Plating	Stainless Steel, Gold	Brass, Gold
Body Plating Specification	MIL-G-45204	

Environmental Specifications

Temperature

Operating Range -55 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to Snap-On MMBX Plug Cable 100 CM Length Using PE-SR405FLJ Coax PE3C5568/HS-100CM](#)



SMA Female to Snap-On MMBX Plug Cable
100 CM Length Using PE-SR405FLJ Coax

RF Cable Assemblies Technical Data Sheet

PE3C5568/HS-100CM

How to Order

Part Number Configuration:

PE3C5568/HS - xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C5568/HS-12 = 12 inches long cable
PE3C5568/HS-100cm = 100 cm long cable

SMA Female to Snap-On MMBX Plug Cable 100 CM Length Using PE-SR405FLJ Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Female to Snap-On MMBX Plug Cable 100 CM Length Using PE-SR405FLJ Coax PE3C5568/HS-100CM](#)


URL: <https://www.pasternack.com/sma-female-mmbx-plug-pe-sr405flj-cable-assembly-pe3c5568-hs-100cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C5568/HS-100CM CAD Drawing

SMA Female to Snap-On MMBX Plug Cable 100 CM Length Using PE-SR405FLJ Coax

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	3/13/2020	SELLIS



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS				THIRD-ANGLE PROJECTION			
TOLERANCES:							
X = ± .2 [.08]		FRACTIONS		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.		SHEET 1 OF 1	
XX = ± .02 [.51]		± 1/32				SCALE N/A	
XXX = ± .005 [.13]		ANGLES ± 1°					
CABLE LENGTH (L) TOLERANCES:							
L ≤ 12 [305] = ± .1 [25] / -0							
12 [305] < L ≤ 60 [1524] = ± .2 [51] / -0							
60 [1524] < L ≤ 120 [3048] = ± .4 [102] / -0							
120 [3048] < L ≤ 300 [7620] = ± .6 [152] / -0							
300 [7620] < L = +5% / -0							
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.				SIZE A		CAGE CODE 53919	
				DRAWN BY K.DANG		ITEM NO. PE3C5568/HS	
						REV A	

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.