



## SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax

## RF Cable Assemblies Technical Data Sheet

PE3W00305-48

**Configuration**

- Connector 1: SHV Plug
- Connector 2: SHV Plug
- Cable Type: RG303

**Features**

- Max Frequency 300 MHz
- FEP Jacket

**Applications**

- General Purpose
- Laboratory Use

**Description**

Pasternack's PE3W00305-48 SHV plug to SHV plug 48 inch cable using RG303 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SHV to SHV cable assembly has a plug to plug gender configuration with 50 ohm flexible RG303 coax. The PE3W00305-48 SHV plug to SHV plug cable assembly operates to 300 MHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		300	MHz
VSWR			1.6:1	
Capacitance		32 [104.99]		pF/ft [pF/m]

**Mechanical Specifications****Cable Assembly**

Length*	48 in [121.92 cm]
Diameter	0.571 in [14.5 mm]

**Cable**

Cable Type	RG303
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax PE3W00305-48](#)



## SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax

### RF Cable Assemblies Technical Data Sheet

PE3W00305-48

Number of Shields	1
Shield Layer 1	Silver Plated Copper Braid
Jacket Material	FEP, Tan
Jacket Diameter	0.17 in [4.32 mm]

#### Connectors

Description	Connector 1	Connector 2
Type	SHV Plug	SHV Plug
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30μ in. minimum	30μ in. minimum
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100μ in. minimum	100μ in. minimum
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100μ in. minimum	100μ in. minimum

#### Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8"$ , whichever is greater.

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax PE3W00305-48](#)




## SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax

### RF Cable Assemblies Technical Data Sheet

PE3W00305-48

#### Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax PE3W00305-48](#)



## SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax

### RF Cable Assemblies Technical Data Sheet

PE3W00305-48

#### How to Order

Part Number Configuration:

**PE3W00305**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3W00305-12 = 12 inches long cable  
PE3W00305-100cm = 100 cm long cable

SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax PE3W00305-48](https://www.pasternack.com/shv-plug-shv-plug-rg303u-cable-assembly-pe3w00305-48-p.aspx)

URL: <https://www.pasternack.com/shv-plug-shv-plug-rg303u-cable-assembly-pe3w00305-48-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W00305-48 CAD Drawing

SHV Plug to SHV Plug Cable 48 Inch Length Using RG303 Coax



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.01
.XXX	±0.005

\*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES



**PASTERNAK®**  
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623  
**Phone:** (949) 261-1920 | **Fax:** (949) 261-7451  
**Website:** [www.pasternack.com](http://www.pasternack.com) | **E-Mail:** [sales@pasternack.com](mailto:sales@pasternack.com)

DWG TITLE	PE3W00305
CAGE CODE	53919

NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].	CAD FILE	07/23/18	SCALE	N/A	SIZE	A	CN2379
---	----------	----------	-------	-----	------	---	--------