



**7/16 DIN Male to N Male Low Loss Cable  
200 cm Length Using LMR-400-UF Coax**

**RF Cable Assemblies Technical Data Sheet**

**PE3W03271-200CM**

**Configuration**

- Connector 1: 7/16 DIN Male
- Connector 2: N Male
- Cable Type: LMR-400-UF

**Features**

- Max Frequency 3 GHz
- Shielding Effectivity > 90 dB
- 85% Phase Velocity
- Double Shielded
- TPE Jacket


**Applications**

- General Purpose
- Laboratory Use

**Description**

Pasternack's PE3W03271-200CM 7/16 DIN male to type N male 200 cm cable using LMR-400-UF coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack 7/16 DIN to type N cable assembly has a male to male gender configuration with 50 ohm flexible LMR-400-UF coax. The PE3W03271-200CM 7/16 DIN male to type N male cable assembly operates to 3 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to N Male Low Loss Cable 200 cm Length Using LMR-400-UF Coax PE3W03271-200CM](#)



## 7/16 DIN Male to N Male Low Loss Cable 200 cm Length Using LMR-400-UF Coax

### RF Cable Assemblies Technical Data Sheet

PE3W03271-200CM

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.5:1	
Velocity of Propagation		85		%
RF Shielding	90			dB
Group Delay		1.2 [3.94]		ns/ft [ns/m]
Capacitance		23.9 [78.41]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor Km]		1.07 [3.51]		Ohms/1000ft [Ohms/
DC Resistance Outer Conductor Km]		1.65 [5.41]		Ohms/1000ft [Ohms/
Jacket Spark			8,000	Vrms

#### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	3	GHz
Insertion Loss (Max.)	0.35	0.43	0.53	0.74	0.78	dB

#### Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax use in this assembly. The Insertion Loss includes an estimated insertion loss of 0.2dB of connector Loss

#### Mechanical Specifications

##### Cable Assembly

Length*	78.74 in [200 cm]
Diameter	1.25 in [31.75 mm]

##### Cable

Cable Type	LMR-400-UF
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to N Male Low Loss Cable 200 cm Length Using LMR-400-UF Coax PE3W03271-200CM](#)



**7/16 DIN Male to N Male Low Loss Cable**  
**200 cm Length Using LMR-400-UF Coax**

**RF Cable Assemblies Technical Data Sheet**

**PE3W03271-200CM**

Jacket Material	TPE, Black
Jacket Diameter	0.405 in [10.29 mm]
One Time Minimum Bend Radius	1 in [25.4 mm]
Repeated Minimum Bend Radius	4 in [101.6 mm]
Bending Moment	0.38 lbs-ft [0.52 N-m]
Flat Plate Crush	20 lbs/in [0.36 Kg/mm]
Tensile Strength	160 lbs [72.57 Kg]

**Connectors**

Description	Connector 1	Connector 2
Type	7/16 DIN Male	N Male
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Silver	Brass, Gold
Contact Plating Specification		50 µ in. minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Body Plating Specification		150 µ in. minimum
Coupling Nut Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Coupling Nut Plating Specification		150 µ in. minimum
Hex Size	1 1/4 inch	13/16 inch

**Mechanical Specification Notes:**

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8"$ , whichever is greater.

**Environmental Specifications**

**Temperature**

Operating Range -40 to +85 deg C

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to N Male Low Loss Cable 200 cm Length Using LMR-400-UF Coax PE3W03271-200CM](#)



7/16 DIN Male to N Male Low Loss Cable  
200 cm Length Using LMR-400-UF Coax

RF Cable Assemblies Technical Data Sheet

PE3W03271-200CM

**How to Order**

Part Number Configuration:

**PE3W03271**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3W03271-12 = 12 inches long cable  
PE3W03271-100cm = 100 cm long cable

7/16 DIN Male to N Male Low Loss Cable 200 cm Length Using LMR-400-UF Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 DIN Male to N Male Low Loss Cable 200 cm Length Using LMR-400-UF Coax PE3W03271-200CM](https://www.pasternack.com/7-16-din-male-n-male-lmr400uf-cable-assembly-pe3w03271-200cm-p.aspx)


URL: <https://www.pasternack.com/7-16-din-male-n-male-lmr400uf-cable-assembly-pe3w03271-200cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE3W03271-200CM CAD Drawing

7/16 DIN Male to N Male Low Loss Cable 200 cm Length Using LMR-400-UF Coax

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/30/19	SELLIS



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS							
TOLERANCES:				THIRD-ANGLE PROJECTION			
X±.2 [5.08]		FRACTIONS					
.XX±.01 [.25]		± 1/32					
.XXX±.005 [.13]		ANGLES ± 1°					
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.							
www.pasternack.com   e-mail: sales@pasternack.com				SIZE		CAGE	
www.pasternack.com				A		53919	
P.O.Box 16759, Irvine, CA 92623.				DRAWN BY		K.DANG	
Phone: 1.949.261.1920   1.866.727.8376				PART NUMBER		PE3W03271	
Fax: 1.949.261.7451				REV		A	
an INFINITE® brand				SHEET		1 OF 1	
				SCALE		N/A	
THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION. ALL RIGHTS RESERVED.							