

# SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax



### RF Cable Assemblies Technical Data Sheet

PE3W05426-24

# Configuration

Connector 1: SMC Plug Right AngleConnector 2: TNC Female Bulkhead

• Cable Type: RG178

### **Features**

- 70% Phase Velocity
- FEP Jacket

# **Applications**

· General Purpose

· Laboratory Use

### Description

Pasternack's PE3W05426-24 SMC plug right angle to TNC female bulkhead 24 inch cable using RG178 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMC to TNC cable assembly has a plug to female gender configuration with 50 ohm flexible RG178 coax. The right angle SMC interface on the RG178 cable allows for easier connections in tight spaces. Our RF cable assembly with TNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

## **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

### **Mechanical Specifications**

### **Cable Assembly**

Length\* 24 in [609.6 mm]

Cable

Cable TypeRG178Impedance50 OhmsInner Conductor TypeStranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTF

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax PE3W05426-24

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



# SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax



# RF Cable Assemblies Technical Data Sheet

PE3W05426-24

Number of Shields Shield Layer 1 Jacket Material Jacket Diameter

FEP, Tan 0.072 in [1.83 mm]

Silver Plated Copper Braid

Repeated Minimum Bend Radius

0.4 in [10.16 mm]

#### **Connectors**

Description	Connector 1	Connector 2	
Туре	SMC Plug Right Angle	TNC Female Bulkhead	
Specification	MIL-STD-348A		
Impedance	50 Ohms	50 Ohms	
Contact Material and Plating	Beryllium Copper, Gold		
Contact Plating Specification	30 μin minimum		
Dielectric Type	PTFE		
Body Material and Plating	Brass, Nickel	Brass, Nickel	
Body Plating Specification	100 µin minimum		
Coupling Nut Material and Plating	Brass, Nickel		
Coupling Nut Plating Specification	100 μin minimum		
Hex Size	1/4 inch		
Torque	3 in-lbs [0.34 Nm]		

Mechanical Specification Notes:

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax PE3W05426-24

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

<sup>\*</sup>All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



# SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax



## RF Cable Assemblies Technical Data Sheet

PE3W05426-24

### **How to Order**



Example: PE3W05426-12 = 12 inches long cable

PE3W05426-100cm = 100 cm long cable

SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax PE3W05426-24

URL: https://www.pasternack.com/smc-plug-tnc-female-rg178bu-cable-assembly-pe3w05426-24-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PE3W05426-24 CAD Drawing
SMC Plug Right Angle to TNC Female Bulkhead Cable 24 Inch Length Using RG178 Coax

