



SMC Plug Right Angle to TNC Female Bulkhead
Cable 50 cm Length Using RG178 Coax

RF Cable Assemblies Technical Data Sheet

PE3W05426-50CM

Configuration

- Connector 1: SMC Plug Right Angle
- Connector 2: TNC Female Bulkhead
- Cable Type: RG178

Features

- 70% Phase Velocity
- FEP Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W05426-50CM SMC plug right angle to TNC female bulkhead 50 cm cable using RG178 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMC to TNC cable assembly has a plug to female gender configuration with 50 ohm flexible RG178 coax. The right angle SMC interface on the RG178 cable allows for easier connections in tight spaces. Our RF cable assembly with TNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

Mechanical Specifications

Cable Assembly

Length* 19.68 in [499.87 mm]

Cable

Cable Type RG178
Impedance 50 Ohms
Inner Conductor Type Stranded
Inner Conductor Material and Plating Copper Clad Steel, Silver
Dielectric Type PTFE

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMC Plug Right Angle to TNC Female Bulkhead Cable 50 cm Length Using RG178 Coax PE3W05426-50CM](#)



SMC Plug Right Angle to TNC Female Bulkhead
Cable 50 cm Length Using RG178 Coax

RF Cable Assemblies Technical Data Sheet

PE3W05426-50CM

Number of Shields	1
Shield Layer 1	Silver Plated Copper Braid
Jacket Material	FEP, Tan
Jacket Diameter	0.072 in [1.83 mm]
Repeated Minimum Bend Radius	0.4 in [10.16 mm]

Connectors

Description	Connector 1	Connector 2
Type	SMC Plug Right Angle	TNC Female Bulkhead
Specification	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	
Contact Plating Specification	30 µin minimum	
Dielectric Type	PTFE	
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 µin minimum	
Coupling Nut Material and Plating	Brass, Nickel	
Coupling Nut Plating Specification	100 µin minimum	
Hex Size	1/4 inch	
Torque	3 in-lbs [0.34 Nm]	

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8"$, whichever is greater.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMC Plug Right Angle to TNC Female Bulkhead Cable 50 cm Length Using RG178 Coax PE3W05426-50CM](#)



SMC Plug Right Angle to TNC Female Bulkhead Cable 50 cm Length Using RG178 Coax

RF Cable Assemblies Technical Data Sheet

PE3W05426-50CM

How to Order

Part Number Configuration:

PE3W05426

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W05426-12 = 12 inches long cable
PE3W05426-100cm = 100 cm long cable

SMC Plug Right Angle to TNC Female Bulkhead Cable 50 cm Length Using RG178 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMC Plug Right Angle to TNC Female Bulkhead Cable 50 cm Length Using RG178 Coax PE3W05426-50CM](https://www.pasternack.com/smc-plug-tnc-female-rg178bu-cable-assembly-pe3w05426-50cm-p.aspx)

URL: <https://www.pasternack.com/smc-plug-tnc-female-rg178bu-cable-assembly-pe3w05426-50cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W05426-50CM CAD Drawing

SMC Plug Right Angle to TNC Female Bulkhead Cable 50 cm Length Using RG178 Coax

