

N Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax



RF Cable Assemblies Technical Data Sheet


PE3W06863-100CM

Configuration

- Connector 1: N Male
- Connector 2: N Male Right Angle
- Cable Type: RG142

Features

- Double Shielded
- FEP Jacket



Applications

· General Purpose

· Laboratory Use

Description

Pasternack's PE3W06863-100CM type N male to type N male right angle 100 cm cable using RG142 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to type N cable assembly has a male to male gender configuration with 50 ohm flexible RG142 coax. The right angle type N interface on the RG142 cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Mechanical Specifications

Cable Assembly

Length* 39.37 in [100 cm]
Diameter 0.83 in [21.08 mm]

Cable

Cable TypeRG142Impedance50 OhmsInner Conductor TypeSolid

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTFE
Number of Shields 2

Shield Layer 1 Silver Plated Copper Braid

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax PE3W06863-100CM

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



N Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax



RF Cable Assemblies Technical Data Sheet

PE3W06863-100CM

Shield Layer 2 Silver Plated Copper Braid

Jacket MaterialFEP, TanJacket Diameter0.195 in [4.95 mm]

Repeated Minimum Bend Radius 1 in [25.4 mm]

Connectors

Description	Connector 1	Connector 2
Туре	N Male	N Male Right Angle
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 μin minimum	30 μin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 μin minimum	100 μin minimum
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100 µin minimum	100 µin minimum

Mechanical Specification Notes:

Environmental Specifications

Temperature

Operating Range -55 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax PE3W06863-100CM

^{*}All cable assemblies have a length tolerance of 1.5% or ± 3/8", whichever is greater.



N Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax



RF Cable Assemblies Technical Data Sheet

PE3W06863-100CM

How to Order



Example: PE3W06863-12 = 12 inches long cable

PE3W06863-100cm = 100 cm long cable

N Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax PE3W06863-100CM

URL: https://www.pasternack.com/n-male-n-male-rg142bu-cable-assembly-pe3w06863-100cm-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PE3W06863-100CM CAD DrawingN Male to N Male Right Angle Cable 100 cm Length Using RG142 Coax

