

BNC Male to SMA Male Right Angle Cable 150 cm
Length Using LMR-240-UF Coax with HeatShrink



RF Cable Assemblies Technical Data Sheet

PE3W07122/HS-150CM

Configuration

- Connector 1: BNC Male
- Connector 2: SMA Male Right Angle
- Cable Type: LMR-240-UF

Features

- Shielding Effectivity > 90 dB
- 84% Phase Velocity
- Double Shielded
- TPE Jacket


Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W07122/HS-150CM BNC male to SMA male right angle 150 cm cable using LMR-240-UF coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to SMA cable assembly has a male to male gender configuration with 50 ohm flexible LMR-240-UF coax. The right angle SMA interface on the LMR-240-UF cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to SMA Male Right Angle Cable 150 cm Length Using LMR-240-UF Coax with HeatShrink PE3W07122/HS-150CM](#)



**BNC Male to SMA Male Right Angle Cable 150 cm
Length Using LMR-240-UF Coax with HeatShrink**

RF Cable Assemblies Technical Data Sheet

PE3W07122/HS-150CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		84		%
RF Shielding	90			dB
Group Delay		1.21 [3.97]		ns/ft [ns/m]
Capacitance		24.2 [79.4]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor Km]		4.28 [14.04]		Ohms/1000ft [Ohms/
DC Resistance Outer Conductor Km]		3.89 [12.76]		Ohms/1000ft [Ohms/
Jacket Spark			5,000	Vrms

Mechanical Specifications

Cable Assembly

Length*	59.05 in [149.99 cm]
Diameter	0.57 in [14.48 mm]

Cable

Cable Type	LMR-240-UF
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	TPE, Black
Jacket Diameter	0.24 in [6.1 mm]
One Time Minimum Bend Radius	0.75 in [19.05 mm]
Repeated Minimum Bend Radius	2.5 in [63.5 mm]
Bending Moment	0.13 lbs-ft [0.18 N-m]
Flat Plate Crush	13 lbs/in [0.23 Kg/mm]
Tensile Strength	80 lbs [36.29 Kg]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to SMA Male Right Angle Cable 150 cm Length Using LMR-240-UF Coax with HeatShrink PE3W07122/HS-150CM](#)



BNC Male to SMA Male Right Angle Cable 150 cm Length Using LMR-240-UF Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3W07122/HS-150CM

Connectors

Description	Connector 1	Connector 2
Type	BNC Male	SMA Male Right Angle
Specification	MIL-STD-348A	MIL-STD-348
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold
Contact Plating Specification	3 μ in minimum	ASTM B488
Dielectric Type	PTFE	Teflon
Body Material and Plating	Brass, Nickel	Brass, Tri-Metal
Body Plating Specification	100 μ in minimum	
Coupling Nut Material and Plating	Brass, Nickel	Brass, Tri-Metal
Coupling Nut Plating Specification	100 μ in minimum	
Hex Size		16-May Inch

Mechanical Specification Notes:

*All cable assemblies have a length tolerance of 1.5% or $\pm 3/8$ ", whichever is greater.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to SMA Male Right Angle Cable 150 cm Length Using LMR-240-UF Coax with HeatShrink PE3W07122/HS-150CM](#)



BNC Male to SMA Male Right Angle Cable 150 cm Length Using LMR-240-UF Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3W07122/HS-150CM

How to Order

Part Number Configuration:

PE3W07122/HS - xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W07122/HS-12 = 12 inches long cable
PE3W07122/HS-100cm = 100 cm long cable

BNC Male to SMA Male Right Angle Cable 150 cm Length Using LMR-240-UF Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to SMA Male Right Angle Cable 150 cm Length Using LMR-240-UF Coax with HeatShrink PE3W07122/HS-150CM](https://www.pasternack.com/bnc-male-sma-male-lmr240uf-cable-assembly-pe3w07122-hs-150cm-p.aspx)

URL: <https://www.pasternack.com/bnc-male-sma-male-lmr240uf-cable-assembly-pe3w07122-hs-150cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W07122/HS-150CM CAD Drawing
BNC Male to SMA Male Right Angle Cable 150 cm Length
Using LMR-240-UF Coax with HeatShrink

