

# TNC Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole



## **RF Connectors Technical Data Sheet**

**PE4065** 

### Configuration

- TNC Female Connector
- MIL-STD-348A
- •50 Ohms
- Straight Body Geometry

#### **Features**

- Max. Operating Frequency 11 GHz
- Gold Plated Brass Contact

Solder Cup Interface Type

• 30 µin minimum contact plating

- Solder Attachment
- Bulkhead

# • Gold Plated Applications

- General Purpose Test
- Rack and Panel Mount Applications

## Description

Pasternack's PE4065 TNC female bulkhead mount connector solder attachment solder cup terminal, .350 inch D hole is part of our full line of RF components available for same-day shipping. Our TNC female connector operates up to a maximum frequency of 11 GHz. This TNC bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our TNC female bulkhead connector PE4065 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable connector assemblies for you and ship same-day.

#### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz
Operating Voltage (AC)			500	Vrms

#### **Mechanical Specifications**

Size

 Length
 1.118 in [28.4 mm]

 Width/Dia.
 0.492 in [12.50 mm]

 Weight
 0.013 lbs [5.9 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole PE4065

ISO 9001 : 2008 Registered

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451



# TNC Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole



### **RF Connectors Technical Data Sheet**

PE4065

#### **Material Specifications**

Description	Material	Plating
Contact	Brass	Gold 30 µin minimum
Insulation	PTFE	
Body	Brass	Nickel 100 μin minimum

#### **Environmental Specifications**

**Temperature** 

**Operating Range** 

-65 to +165 deg C

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

TNC Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole PE4065

URL: https://www.pasternack.com/tnc-female-standard-solder-cup-terminal-connector-pe4065-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



# PE4065 CAD Drawing

TNC Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .350 inch D Hole

