

SSMB Jack Bulkhead Mount Connector Solder Attachment Turret Terminal, .126 inch D Hole, Front Mount



RF Connectors Technical Data Sheet

PE4339

Configuration

- SSMB Jack Connector
- MIL-STD-348A
- •50 Ohms
- Straight Body Geometry

- Turret Interface Type
- Solder Attachment
- Bulkhead

Features

Gold Plated Brass Contact

30 µin minimum contact plating

Applications

• General Purpose Test

Rack and Panel Mount Applications

Description

Pasternack's PE4339 SSMB jack bulkhead mount connector solder attachment turret terminal, .126 inch D hole is part of our full line of RF components available for same-day shipping. This SSMB bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our SSMB jack bulkhead connector PE4339 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable connector assemblies for you and ship same-day.

Mechanical Specifications

Size

 Length
 0.51 in [12.95 mm]

 Width/Dia.
 0.156 in [3.96 mm]

 Weight
 0.002 lbs [0.91 g]

Material Specifications

| Description | Material | Plating |
|-------------|----------|------------------------|
| Contact | Brass | Gold 30 µin minimum |
| Insulation | PTFE | |
| Body | Brass | Gold 30 µin minimum |
| | | |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SSMB Jack Bulkhead Mount Connector Solder Attachment Turret Terminal, .126 inch D Hole, Front Mount PE4339

PE4339 REV 1.1

ISO 9001 : 2008 Registered



SSMB Jack Bulkhead Mount Connector Solder Attachment Turret Terminal, .126 inch D Hole, Front Mount



RF Connectors Technical Data Sheet

PE4339

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SSMB Jack Bulkhead Mount Connector Solder Attachment Turret Terminal, .126 inch D Hole, Front Mount from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SSMB Jack Bulkhead Mount Connector Solder Attachment Turret Terminal, .126 inch D Hole, Front Mount PE4339

URL: https://www.pasternack.com/ssmb-jack-standard-turret-terminal-connector-pe4339-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE4339 CAD Drawing

SSMB Jack Bulkhead Mount Connector Solder Attachment Turret Terminal, .126 inch D Hole, Front Mount

