

SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .018 inch Pin



RF Connectors Technical Data Sheet

PE44025

Configuration

- SMA Female Connector
- MIL-STD-348
- 50 Ohms
- Straight Body Geometry

Features

- Max. Operating Frequency 18 GHz
- Excellent VSWR of 1.25:1

- .018 inch Pin Interface Type
- Field Replaceable Attachment
- 2 Hole Flange

- Gold Plated Beryllium Copper Contact
- Contact plating according to MIL-G-45204

Applications

General Purpose Test

Rack and Panel Mount Applications

Description

Pasternack's PE44025 SMA female 2 hole flange mount field replaceable connector with EMI gasket is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 18 GHz and offers excellent VSWR of 1.25:1. This SMA 2 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. This field replaceable connector is easy to install or replace in the field.

Our SMA female 2 hole flange connector PE44025 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Minimum	Typical	Maximum	Units
DC		18	GHz
		1.25:1	
		71.50	DC 18

Mechanical Specifications

Size

Length 0.375 in [9.53 mm] Width/Dia. 0.223 in [5.66 mm] Height 0.64 in [16.26 mm] Weight 0.006 lbs [2.72 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .018 inch Pin PE44025

ISO 9001 : 2008 Registered



SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .018 inch Pin



RF Connectors Technical Data Sheet

PE44025

Material Specifications

Description	Material	Plating	
Contact	Beryllium Copper	Gold MIL-G-45204	
Insulation	PTFE		
Body	Passivated Stainless Steel	QQ-P-35	

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .018 inch Pin from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .018 inch Pin PE44025

URL: https://www.pasternack.com/sma-female-standard-0.018-pin-connector-pe44025-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE44025 CAD Drawing

SMA Female Field Replaceable Connector With EMI Gasket 2 Hole Flange Mount .018 inch Pin

