

N Female Connector Solder Attachment 2 Hole Flange Mount Tab Terminal, 1.0 inch Hole Spacing



# **RF Connectors Technical Data Sheet**

# PE44078

## Configuration

- N Female Connector
- MIL-STD-348
- 50 Ohms
- Straight Body Geometry

#### Features

- Max. Operating Frequency 11 GHz
- Silver Plated Contact

## **Applications**

General Purpose Test

- Tab Interface Type
  Solder Attachment
- 2 Hole Flange

Contact plating according to QQ-S-365

Rack and Panel Mount Applications

#### Description

Pasternack's PE44078 type N female 2 hole flange mount connector with solder attachment tab terminal (1.0 inch hole spacing) is part of our full line of RF components available for same-day shipping. Our type N female connector operates up to a maximum frequency of 11 GHz. This type N 2 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our type N female 2 hole flange connector PE44078 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

## **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz

#### **Mechanical Specifications**

Size	
Length	0.84 in [21.34 mm]
Width/Dia.	0.64 in [16.26 mm]
Height	1.3 in [33.02 mm]
Weight	0.068 lbs [30.84 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Solder Attachment 2 Hole Flange Mount Tab Terminal, 1.0 inch Hole Spacing PE44078

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com







Mount Tab Terminal, 1.0 inch Hole Spacing




# **RF Connectors Technical Data Sheet**

N Female Connector Solder Attachment 2 Hole Flange

**PE44078** 

# **Material Specifications Material** Description Plating Silver Contact QQ-S-365 PTFE Insulation Body Brass Nickel QQ-N-290 **Environmental Specifications Temperature Operating Range** -65 to +165 deg C Compliance Certifications (see product page for current document) Plotted and Other Data Notes: **Assembly Instruction** N Female Connector Solder Attachment 2 Hole Flange Mount Tab Terminal, 1.0 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Solder Attachment 2 Hole Flange Mount Tab Terminal, 1.0 inch Hole Spacing PE44078 URL: https://www.pasternack.com/n-female-standard-tab-terminal-connector-pe44078-p.aspx The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Sales@Pasternack.com • Techsupport@Pasternack.com





PE44078 CAD Drawing

N Female Connector Solder Attachment 2 Hole Flange

Mount Tab Terminal, 1.0 inch Hole Spacing

