

PASTARACK

SMC Jack Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .232 inch Hole Spacing

TECHNICAL DATA SHEET

PE44143

Configuration	
Connector	SMC Jack
Connector Interface Type	Solder Cup
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Straight
Mount Method	4 Hole Flange
Electrical Specifications	
Impedance, Ohms	50
lechanical Specifications	
Size	
Length, in [mm]	0.575 [14.61]
Width/Dia., in [mm]	0.375 [9.53]
Height, in [mm]	0.375 [9.53]
Weight, Ibs [g]	0.004 [1.81]
Connector	
Туре	SMC Jack
Contact Material and Plating	Gold
Body Material and Plating	Brass, Gold
Dielectric Type	PTFE
Compliance Certifications (visit www.Pasternack.co	om for current document)
RoHS Compliant	Yes
Plotted and Other Data	
Notes:	Values at 25 °C, sea level
	ge Solder Cup Terminal, .232 inch Hole Spacing from Pasterna International orders. Our RF, microwave and fiber optic produc

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Jack Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .232 inch Hole Spacing PE44143

URL: http://www.pasternack.com/smc-jack-standard-solder-cup-terminal-connector-pe44143-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



PE44143 CAD Drawing

SMC Jack Connector Solder Attachment 4 Hole Flange Solder Cup Terminal, .232 inch Hole Spacing

