

75 Ohm TNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Threaded Hole Spacing



RF Connectors Technical Data Sheet

PE44178

Configuration

- TNC Female Connector
- 75 Ohms
- Straight Body Geometry

- Solder Cup Interface Type
- Solder Attachment
- 4 Hole Flange

Features

Gold Plated Brass Contact

• 30 µin minimum contact plating

Applications

• General Purpose Test

Rack and Panel Mount Applications

Description

Pasternack's PE44178 75 ohm TNC female connector solder attachment 4 hole flange mount solder cup terminal. .500 inch threaded hole spacing is part of our full line of RF components available for same-day shipping. This TNC 4 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our 75 ohm TNC female 4 hole flange connector PE44178 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable connector assemblies for you and ship same-day.

Mechanical Specifications

Size

1.063 in [27 mm] Length Width/Dia. 0.687 in [17.45 mm] 0.687 in [17.45 mm] Height Weight 0.027 lbs [12.25 g]

Material Specifications

Description	Material	Plating
Contact	Brass	Gold 30 μin minimum
Insulation	PTFE	
Body	Brass	Nickel 100 µin minimum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm TNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Threaded Hole Spacing PE44178

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered



75 Ohm TNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Threaded Hole Spacing



RF Connectors Technical Data Sheet

PE44178

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm TNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Threaded Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm TNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Threaded Hole Spacing PE44178

URL: https://www.pasternack.com/tnc-female-standard-solder-cup-terminal-connector-pe44178-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



© 2016 Pasternack Enterprises All Rights Reserved

PE44178 CAD Drawing

75 Ohm TNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Threaded Hole Spacing

