

7/16 DIN Male Connector Clamp/Solder Attachment for RG14, RG217



RF Connectors Technical Data Sheet

PE44276

Configuration

- 7/16 DIN Male Connector
- MIL-C-39012
- •50 Ohms
- Straight Body Geometry

- RG14, RG217 Interface Type
 Clamp/Solder Attachment
- 1 1/4 inch Hex

Features

Silver Plated Contact

Contact plating according to QQ-S-365

Applications

• General Purpose Test

Custom Cable Assemblies

Description

Pasternack's PE44276 7/16 DIN male connector with clamp/solder attachment for RG14 and RG217 is part of our full line of RF components available for same-day shipping.

Our 7/16 DIN male connector PE44276 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Mechanical Specifications

Size

 Length
 2.35 in [59.69 mm]

 Width/Dia.
 1.25 in [31.75 mm]

 Weight
 0.336 lbs [152.41 g]

Mating Torque 221 to 265 in-lbs [24.97 to 29.95 Nm]

Material Specifications

Description	Material	Plating
Contact		Silver QQ-S-365
Insulation	PTFE	
Body	Brass	Nickel QQ-N-290
Coupling Nut	Brass	Nickel QQ-N-290

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 7/16 DIN Male Connector Clamp/Solder Attachment for RG14, RG217 PE44276





7/16 DIN Male Connector Clamp/Solder Attachment for RG14, RG217



RF Connectors Technical Data Sheet

PE44276

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

7/16 DIN Male Connector Clamp/Solder Attachment for RG14, RG217 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 7/16 DIN Male Connector Clamp/Solder Attachment for RG14, RG217 PE44276


URL: https://www.pasternack.com/7-16-male-standard-rg14-rg217-connector-pe44276-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.




ASSEMBLY PROCEDURES

ASSEMBLY OF BRAID CLAMP (4). SLIDE BRAID DÓ NOT NICK BRAID WHILE CUTTING (3) OVER CABLE. STRIP CABLE AS JACKET. TAPER END OF BRAID TO PERMIT CLAMP NUT (1), WASHER (2) & CLAMP (4) OVER BRAID & SEAT AGAINST SHOWN. 1. SLIDE GASKET JACKET.



[58,4] 2,30

> 88 BRAID BACK TO SHOULDER. CUT DIÉLECTRIC CENTER CONDUCTOR TO DIMENSION SHOWN. NOT NICK CENTER CONDUCTOR. SOLDER CONTACT TO CENTER CONDUCTOR. REMOVE DIELECTRIC. INSERT CABLE ASSEMBLY INTO EXCESS SOLDER. DO NOT OVER HEAT FORM BRAID OVER CLAMP NUT BODY & TIGHTEN.



PE44276 DWG TITLE

PASTERNACK

Pasternack Enterprises, Inc. P.O. Box 16759 | Irvine | CA | 92623

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
DIMENSIONS ARE IN INCHES [mm]
FITS MIL-C-T7 AND EQUIYALENT CABLES.

53919

147

⋖ SIZE

SCALE N/A

020909

CAD FILE

FSCM NO. REV. A

Website: www.pasternack.com | E-Mail: sales@pasternack.com Phone: (949) 261-1920 | Fax: (949) 261-7451