

### N Male Connector Clamp/Solder Attachment for RG17, RG218, RG219



### **RF Connectors Technical Data Sheet**

PE4433

### Configuration

- N Male Connector
- MIL-STD-348
- 50 Ohms

- Straight Body Geometry
- RG17, RG218, RG219 Interface Type
- Clamp/Solder Attachment

### **Features**

Silver Plated Contact

Contact plating according to QQ-S-365

### **Applications**

• General Purpose Test

Custom Cable Assemblies

### **Description**

Pasternack's PE4433 type N male connector with clamp/solder attachment for RG17, RG218 and RG219 is part of our full line of RF components available for same-day shipping.

Our type N male connector PE4433 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

### **Mechanical Specifications**

Size

Length 2.26 in [57.4 mm] 1.31 in [33.27 mm] Width/Dia. 0.33 lbs [149.69 g] Weight

### **Material Specifications**

Description	Material	Plating
Contact		Silver QQ-S-365
Insulation	PTFE	
Body	Brass	Nickel QQ-N-290
Coupling Nut	Brass	Nickel QQ-N-290

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Connector Clamp/Solder Attachment for RG17, RG218, RG219 PE4433





## N Male Connector Clamp/Solder Attachment for RG17, RG218, RG219



### **RF Connectors Technical Data Sheet**

**PE4433** 

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

N Male Connector Clamp/Solder Attachment for RG17, RG218, RG219 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Connector Clamp/Solder Attachment for RG17, RG218, RG219 PE4433

URL: https://www.pasternack.com/n-male-standard-rg218-connector-pe4433-p.aspx


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.




## **ASSEMBLY PROCEDURES**


SLIDE CLAMP NUT (1) & GASKET (2) OVER CABLE. TAPER END OF BRAID TO PERMIT ASSEMBLY OF BRAID CLAMP (3). SLIDE BRAID CLAMP (3) OVER STRIP CABLE AS SHOWN. DO NOT NICK BRAID WHILE CUTTING JACKET. COMB OUT BRAID. BRAID & SEAT AGAINST JACKET

2.26 [57.4]



REMOVE EXCESS SOLDER. DO NOT OVER HEAT FORM BRAID OVER CLAMP NUT (3). TRIM BRAID CENTER CONDUCTOR TO DIMENSION SHOWN. WASHER (4) & BUSHING (5) OVER DIELECTRIC. SOLDER CONTACT TO CENTER CONDUCTOR. DIELECTRIC. INSERT CABLE ASSEMBLY INTO DO NOT NICK CENTER CONDUCTOR. SLIDE BACK TO SHOULDER. CUT DIELECTRIC & **BODY & TIGHTEN** 





# PASTERNACK

DWG TITLE

Pasternack Enterprises, Inc. P.O. Box 16759 | Irvine | CA | 92623

Website: www.pasternack.com | E-Mail: sales@pasternack.com Phone: (949) 261-1920 | Fax: (949) 261-7451

FSCM NO.

REV. -

53919

CAD FILE

022807

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
DIMENSIONS ARE IN INCHES Imm!
FITS MIL-C-17 AND EQUIVALENT CABLES.

SCALE N/A

SIZE

⋖

2233