

# 75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing



## **RF Connectors Technical Data Sheet**

PE44331

## Configuration

- F Female Connector
- 75 Ohms
- Straight Body Geometry

- Thru Hole Interface Type
- Solder Attachment

#### **Features**

• Tin Plated Brass Contact

# **Applications**

General Purpose Test

PCB Applications

• CATV

#### **Description**

Pasternack's PE44331 75 ohm type F female connector with solder attachment for thru hole PCB (.320 inch x .091 inch hole spacing) is part of our full line of RF components available for same-day shipping.

Our 75 ohm type F female connector PE44331 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### **Mechanical Specifications**

Size

 SIZE

 Length
 1.04 in [26.42 mm]

 Width/Dia.
 0.374 in [9.50 mm]

 Height
 0.374 in [9.5 mm]

 Weight
 0.014 lbs [6.35 g]

#### **Material Specifications**

Description			Material	Plating
Contact			Brass	Tin
Body			Brass	Nickel

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing PE44331

ISO 9001 : 2008 Registered



# 75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing



### RF Connectors Technical Data Sheet

**PE44331** 

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing PE44331

URL: https://www.pasternack.com/f-female-standard-thru-hole-pcb-connector-pe44331-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



# PE44331 CAD Drawing

75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing

