

N Female Connector Solder Attachment Thru Hole PCB, .400 inch x .062 inch Hole Spacing



# **RF Connectors Technical Data Sheet**

## PE44396

### Configuration

- N Female Connector
- MIL-STD-348
- 50 Ohms

#### Features

Silver Plated Contact

- Straight Body GeometryThru Hole Interface Type
- Solder Attachment

Contact plating according to QQ-S-365

### **Applications**

- General Purpose Test
- PCB Applications

#### Description

Pasternack's PE44396 type N female connector with solder attachment for thru hole PCB (.400 inch x .062 inch hole spacing) is part of our full line of RF components available for same-day shipping.

Our type N female connector PE44396 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### **Mechanical Specifications**

Size	
Length	0.968 in [24.59 mm]
Width/Dia.	0.625 in [15.88 mm]
Weight	0.051 lbs [23.13 g]

#### Material Specifications

Description	Material	Plating	
Contact		Silver QQ-S-365	
Insulation	PTFE		
Body	Brass	Nickel QQ-N-290	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Solder Attachment Thru Hole PCB, .400 inch x .062 inch Hole Spacing PE44396

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





N Female Connector Solder Attachment Thru Hole PCB, .400 inch x .062 inch Hole Spacing

# **RF Connectors Technical Data Sheet**



### PE44396

Compliance Certifications (see product page for current document)

#### Plotted and Other Data Notes:

N Female Connector Solder Attachment Thru Hole PCB, .400 inch x .062 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Solder Attachment Thru Hole PCB, .400 inch x .062 inch Hole Spacing PE44396

URL: https://www.pasternack.com/n-female-standard-thru-hole-pcb-connector-pe44396-p.aspx


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



Sales@Pasternack.com • Techsupport@Pasternack.com

PE44396 CAD Drawing

N Female Connector Solder Attachment Thru Hole PCB, .400 inch x .062 inch Hole Spacing



© 2016 Pasternack Enterprises All Rights Reserved

3