

75 Ohm BNC Male Connector Crimp/Solder Attachment for PE-B159, 1855A, Mini 59



# Configuration • PE-B159, 1855A, Mini 59 Interface Type • PE-B159, 1855A, Mini 59 Interface Type • Crimp/Solder Attachment • Straight Body Geometry • Configuration • Max. Operating Frequency 4 GHz • Gold Plated Brass Contact • Opplications • Custom Cable Assemblies • CaTV

### Description

Pasternack's PE44625 75 ohm BNC male connector with crimp/solder attachment for PE-B159, 1855A and Mini 59 is part of our full line of RF components available for same-day shipping. Our BNC male connector operates up to a maximum frequency of 4 GHz.

Our 75 ohm BNC male connector PE44625 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units		
Frequency Range	DC		4	GHz		
Mechanical Specifications						
Size						


Size		
Length		1.18 in [29.97 mm]
Width/Dia.		0.57 in [14.48 mm]
Weight		0.025 lbs [11.34 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm BNC Male Connector Crimp/Solder Attachment for PE-B159, 1855A, Mini 59 PE44625

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com









# **RF Connectors Technical Data Sheet**

75 Ohm BNC Male Connector Crimp/Solder Attachment for PE-B159, 1855A, Mini 59

## PE44625

### Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Nickel
Coupling Nut	Brass	Nickel
Gasket	Rubber	

### **Environmental Specifications**

Temperature Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

### Plotted and Other Data

Notes:

### **Assembly Instruction**

75 Ohm BNC Male Connector Crimp/Solder Attachment for PE-B159, 1855A, Mini 59 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm BNC Male Connector Crimp/Solder Attachment for PE-B159, 1855A, Mini 59 PE44625

URL: https://www.pasternack.com/bnc-male-standard-mini-59-pe-b159-connector-pe44625-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



PE44625 CAD Drawing 75 Ohm BNC Male Connector Crimp/Solder Attachment for PE-B159, 1855A, Mini 59

